

AD9T800603AX

Item Number: AD9T800603AX

Attribute	Value
Brand	Amana
ProductCategory	Unitary
ProductClassPIM	Gas Furnace
System Family	Unitary Split System
Function Category	Heating Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	AD9T80
Short Description	Amana 80% AFUE Gas Furnace Multi-Speed, Two Stage
Model Efficiency	0.8
Product Benefits	Higher reliability and quality; Durable and long igniter life; Provisions for electronic air cleaner and humidifier; Quiet and Economical heating; Energy Efficient and quiet circulation; Self-diagnostic control board with constant memory; Operates on two-stage or single-stage thermostats; Easy Connection for Electronic Humidifier
Product Features - (Standard)	"Heavy-duty stainless-steel tubular heat exchanger"; "Silicon Nitride igniter"; Color-coded low-voltage terminals ; Two-Stage gas valve; Multi-speed ECM blower motor with continuous fan speed; Fault code LED Output; Two-stage gas valve; Furnace control board with self-diagnostics and provisions for electronic air cleaner and 120-volt or 24-volt humidifiers
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051685109
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	6
Long Description	Amana 80% AFUE Gas Furnace Multi-Speed, Two Stage, Downflow/Horizontal, 60,000 BTUH/H, Low NOx
ProductDescriptionPIM	fer cf furnace
AFUE	0.8
CoolingCapacityNominal	36000 Btu/H

Attribute	Value
InstallationConfiguration	Downflow/Horizontal
Producer	No
ProductIDBarcode	AD9T800603AX
TemperatureRiseRangeHigh	25-55 °F
CurrentType	AC
MaxOvercurrentProtection	15 A
MinCircuitAmps	8.7 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
AirFlowRateHighHeating	1155 ft ³ /min
ANSI	Yes
DimensionsBlowerDiameter	10 in
DimensionsBlowerWidth	8 in
DimensionsUnitDepth	28 in
DimensionsUnitHeight	33-3/8 in
DimensionsUnitWidth	14 in
HeatExchangerType	Gas
MotorSpeedType	Multi-Speed
NOxBurnerType	Low NOx
WeightUnit	107 lb
BlowerMotorHorsePower	1/2 metric hp
HighFireInputCapacity	60000 Btu
HighFireOutputCapacity	48000
LowFireInputCapacity	42000
LowFireOutputCapacity	33600
Tonnage	3
GasValveType	Two Stage

Attribute	Value
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	30.00 in
Dimensions - (Case Height)	35.50 in
Dimensions - (Case Width)	15.00 in
Dimensions - (Distribution Unit Depth)	30 in
Dimensions - (Distribution Unit Height)	35.5 in
Dimensions - (Distribution Unit Width)	15 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	35.50 in
Dimensions - (Pallet Width)	45.00 in
Dimensions - (Shipping Unit Depth)	30.00 in
Dimensions - (Shipping Unit Height)	35.50 in
Dimensions - (Shipping Unit Width)	15.00 in
Distribution Shipping Volume - (Unit)	15975 in ³
Shipping Volume - (Unit)	15975.000 in ³
Truck Factor	0
Volume - (Case)	15975.000 in ³
Volume - (Distribution Shipping Unit)	15975 in ³
Weight - (Case)	99.000 lb
Weight - (Distribution Shipping Unit)	99 lb
Weight - (Shipping Unit)	99.000 lb
Registered Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	HEAT EXCHANGER - 79 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 10 YEARS PARTS;ALL PARTS - 10 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS;HEAT EXCHANGER - 79 YEARS PARTS

Attribute	Value
Registered Unit Replacement Warranty - Residential	HEAT EXCHANGER - 10 YEARS UNIT REPLACEMENT;HEAT EXCHANGER - 10 YEARS UNIT REPLACEMENT
Standard Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Gas Furnace
Release Status	Active