

AMVT30BP1300

Item Number: AMVT30BP1300

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Air Handler
System Family	Unitary Split System
Function Category	Air Handler
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	AMVT_32
Series Name	R-32 AMVT
Short Description	R-32 AMVT Air Handler, Variable Speed Motor, Ton
Product Benefits	<p>1. Internal factory-installed thermal expansion valves for cooling and heat pump applications;2. Variable-speed ECM blower motor;3. Integrated communicating ComfortBridge™ Technology;4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud phone and tablet application;5. Auto configuration of the airflow and tonnage in communicating mode;6. Provides constant CFM over a wide range of static pressure conditions independent of duct system;7. CFM indicator;8. Fault recall of six most recent faults;9. Provides adjustable low CFM for efficient fan-only operation;10. Improved humidity and comfort control;11. Built-in compatibility with multi-stage heat pump and cooling applications;12. All-aluminum evaporator coil;13. AHRI certified; ETL listed;14. Rigid SmartFrame™ cabinet;15. Horizontal or vertical configuration capabilities;16. DecaBDE-free thermoplastic drain pan with secondary drain connections;17. Foil-faced insulation covers the internal casing to reduce cabinet condensation;18. Field Installed 3 kW – 25 kW electric heater kits available</p>
Product Features - (Standard)	<p>1. Internal factory-installed thermal expansion valves for cooling and heat pump applications;2. Variable-speed ECM blower motor;3. Integrated communicating ComfortBridge Technology;4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud phone and tablet application. ;5. Auto configuration of the airflow and tonnage in communicating mode;6. Provides constant CFM over a wide range of static pressure conditions independent of duct system;7. CFM indicator;8. Fault recall of six most recent faults;9. Provides adjustable low CFM for efficient fan-only operation;10. Improved humidity and comfort control;11. Built-in compatibility with multi-stage heat pump and cooling applications;12. Optimized for R-32 refrigerant with factory installed leak detection sensor for A2L mitigation.</p>

Attribute	Value
Cabinet Features	1. Rigid SmartFrame™ cabinet;2. Cabinet air leakage less than 2.0% at 1.0 inch H ₂ O when tested in accordance with ASHRAE standard 193;3. Cabinet air leakage less than 1.4% at 0.5 inch H ₂ O when tested in accordance with ASHRAE standard 193;4. Horizontal or vertical configuration capabilities;5. 21" depth for easier attic access;6. DecaBDE-free thermoplastic drain pan with secondary drain connections;7. Screw-less sides and back helps to reduce condensation when installed in humid locations;8. Foil-faced insulation covers the internal casing to reduce cabinet condensation;9. Galvanized, leather grain-embossed finish;10 .Glue-less cabinet insulation retention
Installation Type	Ducted Multi-position
Communication Feature	No
Communication Feature Type	ComfortBridge Technology compatible
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051736375
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	USA
US HTS Code	8415.90.8085
Canadian HTS Code	8415.90.90.00
Long Description	R-32 AMVT Ducted Multi-position Air Handler, Variable Speed Motor, 2.5 Ton, 17-9/16 in Cabinet with TXV Expansion, ComfortBridge Technology compatible
ProductDescriptionPIM	air handler
CoolingCapacityNominal	30000 Btu/H
Producer	Yes
ProductIDBarcode	AMVT30BP1300
IndoorFLA	3.9 A
MaxOvercurrentProtection	50/60 A
MaxVoltage	253 V
MinCircuitAmps	4.9/4.9 A
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	1 Ph

Attribute	Value
PowerVoltage	208/240 V
DimensionsBlowerDiameter	10 in
DimensionsBlowerWidth	6 in
DimensionsUnitDepth	21 in
DimensionsUnitHeight	53-7/16 in
DimensionsUnitWidth	17-9/16 in
ExpansionDevice	TXV
MotorSpeedType	Variable Speed
WeightUnit	134 lb
BlowerMotorHorsePower	0.5 metric hp
TonnageRange	2.5
FactoryStdRefrigerantCharge	0.5 oz
PipeSizeGas	3/4 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	24.50 in
Dimensions - (Case Height)	57.50 in
Dimensions - (Case Width)	18.50 in
Dimensions - (Distribution Unit Depth)	24.5 in
Dimensions - (Distribution Unit Height)	57.5 in
Dimensions - (Distribution Unit Width)	18.5 in
Dimensions - (Pallet Depth)	49.00 in
Dimensions - (Pallet Height)	57.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	24.50 in

Attribute	Value
Dimensions - (Shipping Unit Height)	57.50 in
Dimensions - (Shipping Unit Width)	18.50 in
Distribution Shipping Volume - (Unit)	26061.875 in ³
Shipping Volume - (Unit)	26061.875 in ³
Truck Factor	0
Volume - (Case)	26061.875 in ³
Volume - (Distribution Shipping Unit)	26061.875 in ³
Weight - (Case)	127.000 lb
Weight - (Distribution Shipping Unit)	127 lb
Weight - (Shipping Unit)	127.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Air Handler
Release Status	Active