

MBVK20DP0X00

Item Number: MBVK20DP0X00

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Air Handler
System Family	Unitary Split System
Function Category	Air Handler
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	MBVK
Series Name	Modular Blower
Short Description	Modular Blower Air Handler, Variable Speed ECM Motor, 5 Ton
Product Features - (Standard)	1. Variable-speed ECM blower motor;Compatible with Daikin One+ smart thermostat and other Daikin communicating equipment;3. Advanced configuration of the airflow and tonnage in communicating mode;4. Provides constant CFM over a wide range of static pressure conditions independent of duct system;5. CFM indicator;6. Fault recall of six most recent faults;7. Provides adjustable low CFM for efficient fan-only operation;8. Improved humidity and comfort control;9. Built-in compatibility with multi-stage heat pump and cooling applications;10. Blower section usable as electric heater;11. AHRI certified;12. ETL listed;13. Compatible with both R410A and R32 (use Intergration Kit)
Cabinet Features	1. Horizontal or vertical configuration capabilities;2. 21" depth for easier attic access;3. Foil-faced insulation covers the internal casing to reduce cabinet condensation;4. Galvanized, leather grain-embossed finish;5. Cabinet air leakage less than 2% at 1.0 inch H2O when tested in accordance with ASHRE standard 193;6. Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRE standard 193
Installation Type	Ducted
Communication Feature	Yes
Communication Feature Type	Daikin One+ Smart Thermostat compatible
Export Control Classification Number - (ECCN)	EAR99
Item Stocking Unit of Measure (UOM)	EA

Attribute	Value
Pallet Qty	8
Country of Origin	Mexico
US HTS Code	8414.59.6560
Canadian HTS Code	8414.59.00.92
Long Description	Modular Blower Ducted Air Handler, Variable Speed ECM Motor, 3.55 Ton, 27 in Cabinet with N/A Expansion, Daikin One+ Smart Thermostat compatible
CoolingCapacityNominal	0 Btu/H
InstallationConfiguration	Up-flow, Counterflow and Horizontal
Producer	No
ProductIDBarcode	MBVK20DP0X00
IndoorFLA	8.3 A
MaxOvercurrentProtection	15 A
MaxVoltage	126 V
MinCircuitAmps	10.4 A
MinVoltage	103 V
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
BlowerMotorRPM	2000 r/min
DimensionsBlowerDiameter	11 in
DimensionsBlowerWidth	10 in
DimensionsUnitDepth	21 in
DimensionsUnitHeight	30 in
DimensionsUnitWidth	27 in
EvapMotorRPM	1250 r/min
ExpansionDevice	N/A
IndoorOrificeSize	0 in
MotorSpeedType	Variable Speed ECM

Attribute	Value
WeightUnit	86 lb
BlowerMotorHorsePower	0.75 metric hp
Tonnage	5
TonnageRange	3.5;5
CondensateDrainOutlet	0 in
FactoryStdRefrigerantCharge	0 oz
PipeSizeGas	0 in
PipeSizeLiquid	0 in
RefrigerantType	N/A
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	26.00 in
Dimensions - (Case Height)	32.50 in
Dimensions - (Case Width)	26.00 in
Dimensions - (Distribution Unit Depth)	26 in
Dimensions - (Distribution Unit Height)	32.5 in
Dimensions - (Distribution Unit Width)	26 in
Dimensions - (Pallet Depth)	55.00 in
Dimensions - (Pallet Height)	69.50 in
Dimensions - (Pallet Width)	54.00 in
Dimensions - (Shipping Unit Depth)	26.00 in
Dimensions - (Shipping Unit Height)	32.50 in
Dimensions - (Shipping Unit Width)	26.00 in
Shipping Volume - (Unit)	21970.000 in ³
Truck Factor	0
Volume - (Case)	21970.000 in ³
Volume - (Distribution Shipping Unit)	21970 in ³

Attribute	Value
Weight - (Case)	86.090 lb
Weight - (Distribution Shipping Unit)	86.09 lb
Weight - (Shipping Unit)	86.090 lb