

## 2MX18AXVJU

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Multi-Split Heat Pump
<b>System Family</b>	Multi-Split
<b>Function Category</b>	Heat Pump
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Outdoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	2MX_AXVJU
<b>Series Name</b>	Daikin CIRRA Multi-Zone System
<b>Short Description</b>	Multi Split Heat Pump Outdoor Series Outdoor Multi-Split Heat Pump
<b>Family Description</b>	1.5 Ton 2-Port Heat Pump Up to 17 SEER / 9 HSPF / 10 EER
<b>Product Benefits</b>	10 Year limited parts warranty with online registration;5 Year limited parts warranty for commercial applications
<b>Product Features - (Standard)</b>	Inverter Technology delivers precise temperature control and superior energy efficiency
<b>Communication Feature</b>	No
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	8
<b>Country of Origin</b>	Malaysia
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>ProductDescriptionPIM</b>	Daikin CIRRA 2 Port Heat Pump, Ductless ODU 1.5 Ton
<b>COP47NonDucted</b>	3.5
<b>EERNonDucted</b>	10
<b>HSPFNonDucted</b>	9

Attribute	Value
<b>SEERNonDucted</b>	17
<b>Producer</b>	No
<b>ProductIDBarcode</b>	2MX18AXVJU
<b>CoolingOperationRangeStdMax</b>	114.8 °F
<b>CoolingOperationRangeStdMin</b>	50 °F
<b>HeatingOperationRangeStdMax</b>	64.4 °F
<b>HeatingOperationRangeStdMin</b>	5 °F
<b>RatedCoolingConditionAmbientDB</b>	95 °F
<b>RatedCoolingConditionAmbientWB</b>	75 °F
<b>RatedCoolingConditionRoomDB</b>	80 °F
<b>RatedCoolingConditionRoomWB</b>	67 °F
<b>RatedHeatingConditionAmbientDB</b>	47 °F
<b>RatedHeatingConditionAmbientWB</b>	43 °F
<b>RatedHeatingConditionRoomDB</b>	70 °F
<b>RatedHeatingConditionRoomWB</b>	60 °F
<b>CompressorRLA</b>	9.5 A
<b>InterConnectingWires</b>	L1, L2, L3, Ground
<b>MaxOvercurrentProtection</b>	15 A
<b>MaxStartingCurrent</b>	9.5 A
<b>MinCircuitAmps</b>	10.9 A
<b>OutdoorFLA</b>	0.44 A
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208-230 V
<b>AirFlowRateHighCooling</b>	1170 ft <sup>3</sup> /min
<b>AirFlowRateHighHeating</b>	1300 ft <sup>3</sup> /min

Attribute	Value
<b>CompressorStages</b>	Inverter
<b>CompressorType</b>	Swing
<b>DimensionsUnitDepth</b>	11-3/16 in
<b>DimensionsUnitHeight</b>	21-11/16 in
<b>DimensionsUnitWidth</b>	26-1/2 in
<b>HeatExchangerType</b>	Air Cooled
<b>MaxIndoorUnits</b>	2
<b>SoundPressureHighCooling</b>	51 dBA
<b>SoundPressureHighHeating</b>	56 dBA
<b>WeightUnit</b>	77 lb
<b>CoolingCapacityRated</b>	17000 Btu/H
<b>CoolingInputPower</b>	1.7 kW
<b>HeatingCapacityRated</b>	17000 Btu/H
<b>HeatingInputPower</b>	1.424 kW
<b>Tonnage</b>	1.5
<b>FactoryStdRefrigerantCharge</b>	2.65 lb
<b>MaxPipeLengthTotal</b>	98.5 ft
<b>MaxPipeLengthVertical</b>	49.25 ft
<b>PipeSizeGas</b>	3/8 in
<b>PipeSizeLiquid</b>	1/4 in
<b>RatedHeightDifference</b>	0 ft
<b>RatedPipingLength</b>	25 ft
<b>RefrigerantOil</b>	PVE (FVC50K)
<b>RefrigerantPreChargedLineLength</b>	98.5 ft
<b>RefrigerantType</b>	R-410A
<b>Proposition 65 Label</b>	Yes
<b>Carton Type</b>	CTN
<b>Case Qty</b>	1

Attribute	Value
<b>Dimensions - (Case Depth)</b>	31.50 in
<b>Dimensions - (Case Height)</b>	24.00 in
<b>Dimensions - (Case Width)</b>	15.25 in
<b>Dimensions - (Distribution Unit Depth)</b>	31.5 in
<b>Dimensions - (Distribution Unit Height)</b>	24 in
<b>Dimensions - (Distribution Unit Width)</b>	15.25 in
<b>Dimensions - (Pallet Depth)</b>	62.00 in
<b>Dimensions - (Pallet Height)</b>	53.00 in
<b>Dimensions - (Pallet Width)</b>	32.00 in
<b>Dimensions - (Shipping Unit Depth)</b>	31.50 in
<b>Dimensions - (Shipping Unit Height)</b>	24.00 in
<b>Dimensions - (Shipping Unit Width)</b>	15.25 in
<b>Distribution Shipping Volume - (Unit)</b>	11529 in <sup>3</sup>
<b>Shipping Volume - (Unit)</b>	11529.000 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	11529.000 in <sup>3</sup>
<b>Volume - (Distribution Shipping Unit)</b>	11529 in <sup>3</sup>
<b>Weight - (Case)</b>	84.000 lb
<b>Weight - (Distribution Shipping Unit)</b>	84 lb
<b>Weight - (Shipping Unit)</b>	84.000 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 10 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 10 YEARS PARTS

Attribute	Value
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Multi-Split/Multi-Split Heat Pump
<b>Release Status</b>	Obsolete