

4MXLH36WVJU9

Attribute	Value
Brand	Daikin
ProductCategory	Ductless Mini-Splits
ProductClassPIM	Multi-Split Heat Pump
System Family	Multi-Split
Function Category	Heat Pump
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	4MXLH_WVJU9
Series Name	AURORA
Short Description	Multi Split Heat Pump Outdoor Series Outdoor Multi-Split Heat Pump
Family Description	3.0 Ton 4-Port Heat Pump
Product Benefits	"12 Year Limited Parts Warranty w/ online registration PAM control Energy efficient operation Quiet outdoor unit operation Unit performs self diagnosis and indicates using LED lights""""
Product Features - (Standard)	" Built in Drain Pan Heater, 4 Zone enhanced Capacity Multi-Zone Night Quiet Mode Automatic Defrost Quick Warming Function Automatic Defrosting Priority Room Setting Cool/Heat mode lock Self Diagnosis Wiring error check function Anti-corrosion treatment of outdoor heat exchanger""""
Communication Feature	No
Export Control Classification Number - (ECCN)	EAR99
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	Thailand

Attribute	Value
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	AURORA 4 port hp, ductless od 3 Ton with built in Drain Pan Heater
AHRIReferenceNumber	212604426
COP47Ducted	3.3
COP47NonDucted	4.26
EER2Ducted	9.3
EER2NonDucted	11.7
ENERGYSTARCertified	No
HSPF2Ducted	7.8
HSPF2NonDucted	8.8
SEER2Ducted	15.9
SEER2NonDucted	20
Producer	No
ProductIDBarcode	4MXLH36WVJU9
CoolingOperationRangeStdMax	114.8 °F
CoolingOperationRangeStdMin	14 °F
HeatingOperationRangeStdMax	60 °F
HeatingOperationRangeStdMin	-13 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
RatedHeatingConditionAmbientDB	47 °F
RatedHeatingConditionAmbientWB	43 °F
RatedHeatingConditionRoomDB	70 °F

Attribute	Value
RatedHeatingConditionRoomWB	60 °F
CompressorRLA	27.0 A
FanMotorOutput	126
FuseSize	35 A
InterConnectingWires	L1, L2, L3, Ground
MaxOvercurrentProtection	35 A
MaxStartingCurrent	27 A
MinCircuitAmps	30.2 A
OutdoorFLA	0.76 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208-230 V
RatedLoadAmps	27 A
AirFlowRateHighCooling	3684 ft ³ /min
AirFlowRateHighHeating	3356 ft ³ /min
AirFlowRateLowCooling	2756 ft ³ /min
AirFlowRateLowHeating	1500 ft ³ /min
AirFlowRateMediumCooling	3029 ft ³ /min
AirFlowRateMediumHeating	3138 ft ³ /min
CompressorStages	Inverter
CompressorType	Swing
DimensionsUnitDepth	18-1/8 in
DimensionsUnitHeight	34-1/4 in
DimensionsUnitWidth	43-5/16 in
ExpansionDevice	EEV
HeatExchangerType	Air Cooled
MaxIndoorUnits	4
SoundPressureHighCooling	53 dBA

Attribute	Value
SoundPressureHighHeating	55 dBA
WeightUnit	216 lb
CoolingCapacityMax	40500 Btu/H
CoolingCapacityMin	8300 Btu/H
CoolingCapacityRated	34400 Btu/H
HeatingCapacityRated	36600 Btu/H
Tonnage	3
AdditionalRefrigerantCharge	0.21 lb
CondensateDrainOutlet	5/8 in
FactoryStdRefrigerantCharge	8.6 oz
MaxIndoorToIndoorPiping	98 ft
MaxPipeLengthTotal	230 ft
MaxPipeLengthVertical	49.25 ft
NumberOfConnectionPorts	4
PipeSizeGas	3/8 in
PipeSizeLiquid	1/4 in
RatedHeightDifference	0 ft
RatedPipingLength	25 ft
RefrigerantOil	PVE (FVC50K)
RefrigerantPreChargedLineLength	131.2 ft
RefrigerantType	R-410A
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	47.00 in
Dimensions - (Case Height)	40.00 in
Dimensions - (Case Width)	22.00 in

Attribute	Value
Dimensions - (Distribution Unit Depth)	47 in
Dimensions - (Distribution Unit Height)	40 in
Dimensions - (Distribution Unit Width)	22 in
Dimensions - (Pallet Depth)	48.00 in
Dimensions - (Pallet Height)	85.00 in
Dimensions - (Pallet Width)	45.00 in
Dimensions - (Shipping Unit Depth)	47.00 in
Dimensions - (Shipping Unit Height)	40.00 in
Dimensions - (Shipping Unit Width)	22.00 in
Distribution Shipping Volume - (Unit)	41360 in ³
Shipping Volume - (Unit)	41360.000 in ³
Truck Factor	0
Volume - (Case)	41360.000 in ³
Volume - (Distribution Shipping Unit)	41360 in ³
Weight - (Case)	230.000 lb
Weight - (Distribution Shipping Unit)	230 lb
Weight - (Shipping Unit)	230.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 12 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 12 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS

Attribute	Value
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Multi-Split/Multi-Split Heat Pump
Release Status	Active