

# AHVE24BP1300

Attribute	Value
<b>Brand</b>	Corporate
<b>ProductCategory</b>	Unitary
<b>ProductClassPIM</b>	Air Handler
<b>System Family</b>	Unitary Split System
<b>Function Category</b>	Air Handler
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	AHVE230V_32
<b>Series Name</b>	Inverter compatible Air Handler
<b>Short Description</b>	Inverter compatible Air Handler Air Handler, Variable Speed Motor, Ton
<b>Product Features - (Standard)</b>	<p>Electronic Expansion Valve (EEV) for cooling and heat pump applications;7 mm evaporator coil tube size;Variable-speed ECM blower motor;Compatible with Daikin One+ smart thermostat and other Daikin communicating equipment;Provides constant CFM over a wide range of static pressure conditions independent of duct system;CFM indicator;Thermostat provides adjustable low CFM for efficient fan-only operation;All-aluminum evaporator coil;Fault recall of six most recent faults;Improved humidity and comfort control;AHRI certified;ETL listed;Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193;Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRAE standard 193;3 kW – 25 kW electric heater kits;Horizontal or vertical configuration capabilities;21" depth for easier attic access;DecaBDE-free thermoplastic drain pan with secondary drain connections;Screw-less sides and back helps to reduce condensation when installed in humid locations;Foil-faced insulation covers the internal casing to reduce cabinet condensation;Galvanized, leather grain-embossed finish;Glue-less cabinet insulation retention;Tool-less filter access</p>

Attribute	Value
<b>Cabinet Features</b>	<ul style="list-style-type: none"> <li>• Cabinet air leakage less than 2.0% at 1.0 inch H<sub>2</sub>O when tested in accordance with ASHRAE standard 193</li> <li>• Cabinet air leakage less than 1.4% at 0.5 inch H<sub>2</sub>O when tested in accordance with ASHRAE standard 193</li> <li>• 3 kW – 25 kW electric heater kits</li> <li>• Horizontal or vertical configuration capabilities</li> <li>• 21" depth for easier attic access</li> <li>• DecaBDE-free thermoplastic drain pan with secondary drain connections</li> <li>• Screw-less sides and back helps to reduce condensation when installed in humid locations</li> <li>• Foil-faced insulation covers the internal casing to reduce cabinet condensation</li> <li>• Galvanized, leather grain-embossed finish</li> <li>• Glue-less cabinet insulation retention</li> <li>• Tool-less filter access</li> </ul>
<b>Installation Type</b>	Ducted Multi-position
<b>Communication Feature</b>	Yes
<b>Communication Feature Type</b>	ComfortNet Compatible
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Universal Product Code (UPC)</b>	663051735170
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	4
<b>Country of Origin</b>	USA
<b>US HTS Code</b>	8415.90.8085
<b>Canadian HTS Code</b>	8415.90.90.00
<b>Long Description</b>	Inverter compatible Air Handler Ducted Multi-position Air Handler, Variable Speed Motor, 2 Ton, 17-1/2 in Cabinet with EEV Expansion, ComfortNet Compatible
<b>ProductDescriptionPIM</b>	Air Handler, Inverter, 2 Ton_R32
<b>CoolingCapacityNominal</b>	24000 Btu/H
<b>Producer</b>	Yes
<b>ProductIDBarcode</b>	AHVE24BP1300
<b>IndoorFLA</b>	3.9 A
<b>MaxOvercurrentProtection</b>	15/15 A
<b>MaxVoltage</b>	253 V
<b>MinCircuitAmps</b>	4.9/4.9 A

Attribute	Value
<b>MinVoltage</b>	197 V
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208/230 V
<b>DimensionsBlowerDiameter</b>	9.5 in
<b>DimensionsBlowerWidth</b>	6 in
<b>DimensionsUnitDepth</b>	21 in
<b>DimensionsUnitHeight</b>	45 in
<b>DimensionsUnitWidth</b>	17-1/2 in
<b>DimensionsWheelDiameter</b>	9.5 in
<b>DimensionsWheelWidth</b>	6 in
<b>EvapCoilFaceArea</b>	3.06
<b>EvapMotorRPM</b>	1250 r/min
<b>ExpansionDevice</b>	EEV
<b>MotorSpeedType</b>	Variable Speed
<b>NumberOfSpeeds</b>	Variable
<b>WeightUnit</b>	115 lb
<b>BlowerMotorHorsePower</b>	0.5 metric hp
<b>TonnageRange</b>	2
<b>FactoryStdRefrigerantCharge</b>	0 oz
<b>PipeSizeGas</b>	3/4 in
<b>PipeSizeLiquid</b>	3/8 in
<b>RefrigerantType</b>	R-32
<b>Proposition 65 Label</b>	Yes
<b>Carton Type</b>	CTN
<b>Case Qty</b>	1
<b>Dimensions - (Case Depth)</b>	24.50 in
<b>Dimensions - (Case Height)</b>	49.00 in

Attribute	Value
<b>Dimensions - (Case Width)</b>	18.50 in
<b>Dimensions - (Distribution Unit Depth)</b>	24.5 in
<b>Dimensions - (Distribution Unit Height)</b>	49 in
<b>Dimensions - (Distribution Unit Width)</b>	18.5 in
<b>Dimensions - (Pallet Depth)</b>	49.00 in
<b>Dimensions - (Pallet Height)</b>	49.00 in
<b>Dimensions - (Pallet Width)</b>	37.00 in
<b>Dimensions - (Shipping Unit Depth)</b>	24.50 in
<b>Dimensions - (Shipping Unit Height)</b>	49.00 in
<b>Dimensions - (Shipping Unit Width)</b>	18.50 in
<b>Distribution Shipping Volume - (Unit)</b>	22209.25 in <sup>3</sup>
<b>Shipping Volume - (Unit)</b>	22209.250 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	22209.250 in <sup>3</sup>
<b>Volume - (Distribution Shipping Unit)</b>	22209.25 in <sup>3</sup>
<b>Weight - (Case)</b>	114.000 lb
<b>Weight - (Distribution Shipping Unit)</b>	116.09 lb
<b>Weight - (Shipping Unit)</b>	114.000 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 10 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 10 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS

Attribute	Value
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Residential Split System/Air Handler
<b>Release Status</b>	Active