

# ASPT37C14

Attribute	Value
<b>Brand</b>	Corporate
<b>ProductCategory</b>	Unitary
<b>ProductClassPIM</b>	Air Handler
<b>System Family</b>	Unitary Split System
<b>Function Category</b>	Air Handler
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	ASPT
<b>Series Name</b>	ASPT
<b>Short Description</b>	ASPT Air Handler, Fixed Speed ECM Motor, 3 Ton
<b>Family Description</b>	Multi-Position, Multi-Speed, ECM-Based Air Handler with Internal TXV 1½ to 5 Tons
<b>Product Benefits</b>	1. Check flowrate for heat pump and cooling-only applications;2. All-Aluminum tube/aluminum fin coil;3. Direct-drive, resilient-mount, multi-speed motor;4. Available without heat or with sequence-controlled and rust-resistant nickel chromium heating elements of 5, 6, 8, 10 or 15 kW;5. High-efficiency evaporator coil;6. Quiet operation;7. Models with PSC motors;8. Primary/secondary drain connection in a high-temperature plastic drain pan;9. Suitable for free-return installation (non-ducted return air);10. Galvanized-steel construction;11. Factory-installed pull-type disconnect;12. Easy service access;13. AHRI Certified; ETL Listed
<b>Product Features - (Standard)</b>	1. Internal factory-installed thermal expansion valves for cooling and heat pump applications;2. Direct drive, multi-speed ECM blower motor;3. All-aluminum evaporator coil;4. Coil mounting track for quick repositioning;5. Optimized for use with R-410A refrigerant;6. Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193;7. Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRAE standard 193;8. 5 kW – 15 kW electric heater kits;9. AHRI certified;10. ETL listed
<b>Cabinet Features</b>	1. Rigid SmartFrame cabinet;2. Horizontal or vertical configuration capabilities;3. 21" depth for easier attic access;4. DecaBDE-free thermoplastic drain pan with secondary drain connections;5. Screw-less sides and back helps to reduce condensation when installed in humid locations;6. Foil-faced insulation covers the internal casing to reduce cabinet condensation;7. Galvanized, leather grain-embossed finish;8. Glue-less cabinet insulation retention;9. Tool-less filter access
<b>Installation Type</b>	Ducted Multi-position
<b>Communication Feature</b>	No

Attribute	Value
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Min Advertised Price</b>	1233 \$
<b>Serialized Flag</b>	Yes
<b>Universal Product Code (UPC)</b>	663051559608
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	4
<b>Country of Origin</b>	USA
<b>US HTS Code</b>	8415.90.8085
<b>Canadian HTS Code</b>	8415.90.90.00
<b>Long Description</b>	ASPT Ducted Multi-position Air Handler, Fixed Speed ECM Motor, 3 Ton, 21 in Cabinet with TXV Expansion,
<b>ProductDescriptionPIM</b>	3 Ton, Multi-Position, Multi-Speed ECM, Air Handler
<b>CoolingCapacityNominal</b>	36000 Btu/H
<b>Producer</b>	Yes
<b>ProductIDBarcode</b>	ASPT37C14
<b>CurrentType</b>	AC
<b>IndoorFLA</b>	4.5 A
<b>MaxOvercurrentProtection</b>	15 A
<b>MaxVoltage</b>	253 V
<b>MinCircuitAmps</b>	5.6/5.6 A
<b>MinVoltage</b>	197 V
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208/240 V
<b>BlowerMotorRPM</b>	1250 r/min
<b>DimensionsBlowerDiameter</b>	10-5/8 in
<b>DimensionsBlowerWidth</b>	8 in
<b>DimensionsUnitDepth</b>	21 in

Attribute	Value
DimensionsUnitHeight	53-1/2 in
DimensionsUnitWidth	21 in
EnergySource	Electric
ETLListed	Yes
ExpansionDevice	TXV
HeatExchangerType	Air Cooled
MotorSpeedType	Fixed Speed ECM
WeightUnit	144 lb
BlowerMotorHorsePower	3/4 metric hp
Tonnage	3
TonnageRange	3
CondensateDrainOutlet	3/4 in
PipeSizeGas	7/8 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-410A
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	23.00 in
Dimensions - (Case Height)	57.50 in
Dimensions - (Case Width)	22.00 in
Dimensions - (Distribution Unit Depth)	23 in
Dimensions - (Distribution Unit Height)	57.5 in
Dimensions - (Distribution Unit Width)	22 in
Dimensions - (Pallet Depth)	46.00 in
Dimensions - (Pallet Height)	57.50 in
Dimensions - (Pallet Width)	44.00 in

Attribute	Value
<b>Dimensions - (Shipping Unit Depth)</b>	23.00 in
<b>Dimensions - (Shipping Unit Height)</b>	57.50 in
<b>Dimensions - (Shipping Unit Width)</b>	22.00 in
<b>Distribution Shipping Volume - (Unit)</b>	29095 in <sup>3</sup>
<b>Shipping Volume - (Unit)</b>	29095.000 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	29095.000 in <sup>3</sup>
<b>Volume - (Distribution Shipping Unit)</b>	29095 in <sup>3</sup>
<b>Weight - (Case)</b>	147.000 lb
<b>Weight - (Distribution Shipping Unit)</b>	147 lb
<b>Weight - (Shipping Unit)</b>	147.000 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 10 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 10 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Residential Split System/Air Handler
<b>Release Status</b>	Obsolete