

AVPTC61D14

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Air Handler
System Family	Unitary Split System
Function Category	Air Handler
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	AVPTC
Series Name	AVPTC
Short Description	AVPTC Air Handler, Variable Speed ECM
Family Description	Multi-Position, Variable-Speed, ECM-Based Air Handler with Internal TXV ComfortBridge™ Compatible 1½ to 5 Tons
Product Benefits	<p>1. Internal factory-installed thermal expansion valves for cooling and heat pump applications;2. Variable-speed ECM blower motor;3. Integrated communicating ComfortBridge™ Technology;4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud phone and tablet application;5. Auto configuration of the airflow and tonnage in communicating mode;6. Provides constant CFM over a wide range of static pressure conditions independent of duct system;7. CFM indicator;8. Fault recall of six most recent faults;9. Provides adjustable low CFM for efficient fan-only operation;10. Improved humidity and comfort control;11. Built-in compatibility with multi-stage heat pump and cooling applications;12. All-aluminum evaporator coil;13. AHRI certified; ETL listed;14. Rigid SmartFrame™ cabinet;15. Horizontal or vertical configuration capabilities;16. DecaBDE-free thermoplastic drain pan with secondary drain connections;17. Foil-faced insulation covers the internal casing to reduce cabinet condensation;18. Field Installed 5 kW – 25 kW electric heater kits available</p>
Product Features - (Standard)	<p>1. Internal factory-installed thermal expansion valves for cooling and heat pump applications;2. Variable-speed ECM blower motor;3. Integrated communicating ComfortBridge™ Technology;4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud phone and tablet application. ;5. Auto configuration of the airflow and tonnage in communicating mode;6. Provides constant CFM over a wide range of static pressure conditions independent of duct system;7. CFM indicator;8. Fault recall of six most recent faults;9. Provides adjustable low CFM for efficient fan-only operation;10. Improved humidity and comfort control;11. Built-in compatibility with multi-stage heat pump and cooling applications</p>

Attribute	Value
Cabinet Features	1. Rigid SmartFrame™ cabinet;2. Cabinet air leakage less than 2.0% at 1.0 inch H ₂ O when tested in accordance with ASHRAE standard 193;3. Cabinet air leakage less than 1.4% at 0.5 inch H ₂ O when tested in accordance with ASHRAE standard 193;4. Horizontal or vertical configuration capabilities;5. 21" depth for easier attic access;6. DecaBDE-free thermoplastic drain pan with secondary drain connections;7. Screw-less sides and back helps to reduce condensation when installed in humid locations;8. Foil-faced insulation covers the internal casing to reduce cabinet condensation;9. Galvanized, leather grain-embossed finish;10 .Glue-less cabinet insulation retention
Installation Type	Ducted Multi-position
Communication Feature	Yes
Communication Feature Type	ComfortBridge Technology compatible
Export Control Classification Number - (ECCN)	EAR99
Min Advertised Price	1764 \$
Serialized Flag	Yes
Universal Product Code (UPC)	663051609570
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	USA
US HTS Code	8415.90.8085
Canadian HTS Code	8415.90.90.00
Long Description	AVPTC Ducted Multi-position Air Handler, Variable Speed ECM Motor, Ton, 24-1/2 in Cabinet with TXV Expansion, ComfortBridge Technology compatible
ProductDescriptionPIM	air handler
CoolingCapacityNominal	60000 Btu/H
Producer	Yes
ProductIDBarcode	AVPTC61D14
CurrentType	AC
IndoorFLA	6.9 A
MaxOvercurrentProtection	15 A
MaxVoltage	253 V
MinCircuitAmps	8.6/8.6 A

Attribute	Value
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208/240 V
BlowerMotorRPM	1250 r/min
DimensionsBlowerDiameter	11-5/16 in
DimensionsBlowerWidth	10-5/8 in
DimensionsUnitDepth	21 in
DimensionsUnitHeight	58 in
DimensionsUnitWidth	24-1/2 in
EnergySource	Electric
ExpansionDevice	TXV
MotorSpeedType	Variable Speed ECM
WeightUnit	167 lb
BlowerMotorHorsePower	1 metric hp
Tonnage	5
CondensateDrainOutlet	3/4 in
PipeSizeGas	7/8 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-410A
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	24.50 in
Dimensions - (Case Height)	62.00 in
Dimensions - (Case Width)	26.00 in
Dimensions - (Distribution Unit Depth)	24.5 in

Attribute	Value
Dimensions - (Distribution Unit Height)	62 in
Dimensions - (Distribution Unit Width)	26 in
Dimensions - (Pallet Depth)	49.00 in
Dimensions - (Pallet Height)	62.00 in
Dimensions - (Pallet Width)	52.00 in
Dimensions - (Shipping Unit Depth)	24.50 in
Dimensions - (Shipping Unit Height)	62.00 in
Dimensions - (Shipping Unit Width)	26.00 in
Distribution Shipping Volume - (Unit)	39494 in ³
Shipping Volume - (Unit)	39494.000 in ³
Truck Factor	0
Volume - (Case)	39494.000 in ³
Volume - (Distribution Shipping Unit)	39494 in ³
Weight - (Case)	162.000 lb
Weight - (Distribution Shipping Unit)	162 lb
Weight - (Shipping Unit)	162.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS

Attribute	Value
Ecomm Path Display	Equipment/Residential Split System/Air Handler
Release Status	Active