

## CAPTA6034C3

Attribute	Value
<b>Brand</b>	Corporate
<b>ProductCategory</b>	Unitary
<b>ProductClassPIM</b>	Coil
<b>System Family</b>	Unitary Split System
<b>Function Category</b>	Cooling Only
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	CAPTA_3
<b>Series Name</b>	CAPTA AlumaFin7™
<b>Short Description</b>	CAPTA AlumaFin7™ Evaporator Coil, Upflow/Downflow, Ton, R-32
<b>Family Description</b>	CAPTA AlumaFin7™ Evaporator Coil
<b>Product Features - (Standard)</b>	All-Aluminum evaporator coil ;Optimized for use with R-32 refrigerant including circuits and manifolds;R-32 sensor designed for the life span of the coil;Factory-installed thermal expansion valves for cooling and heat pump applications;Standardized copper suction tube stub length;Check flowrator for cooling and heat pump applications;Vertical application;21" depth for easier attic access;Single front access panel;Foil-faced insulation covers the internal casing to reduce cabinet condensation;Galvanized, leather grain-embossed finish;Rust resistant, thermoplastic drain pan featuring a low water-retention design;DecaBDE-free thermoplastic drain pan with secondary drain connections;Drain pan rails designed to remove and reposition coils with ease without compromising structural integrity;UV-resistant drain pan;AHRI certified;ETL Listed
<b>Installation Type</b>	Ducted
<b>Communication Feature</b>	No
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Universal Product Code (UPC)</b>	663051848290
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	8
<b>Country of Origin</b>	USA

Attribute	Value
<b>Long Description</b>	CAPTA AlumaFin7™ Cased Evaporator Coil, Upflow/Downflow, 5 Ton, 21 in Cabinet with TXV Expansion, R-32
<b>ProductDescriptionPIM</b>	5T Cased Upflow/Downflow R-32 Coil with TXV
<b>ENERGYSTARCertified</b>	No
<b>Producer</b>	No
<b>ProductIDBarcode</b>	CAPTA6034C3
<b>CasedvsUncased</b>	Cased
<b>DimensionsUnitDepth</b>	21 in
<b>DimensionsUnitHeight</b>	34 in
<b>DimensionsUnitWidth</b>	21 in
<b>ExpansionDevice</b>	TXV
<b>IndoorOrificeSize</b>	N/A in
<b>WeightUnit</b>	77 lb
<b>TonnageRange</b>	5
<b>CondensateDrainOutlet</b>	3/4 in
<b>PipeSizeGas</b>	7/8 in
<b>PipeSizeLiquid</b>	3/8 in
<b>RefrigerantType</b>	R-32
<b>Proposition 65 Label</b>	Yes
<b>Carton Type</b>	CTN
<b>Case Qty</b>	1
<b>Dimensions - (Case Depth)</b>	26.00 in
<b>Dimensions - (Case Height)</b>	36.00 in
<b>Dimensions - (Case Width)</b>	23.50 in
<b>Dimensions - (Pallet Depth)</b>	54.00 in
<b>Dimensions - (Pallet Height)</b>	78.00 in
<b>Dimensions - (Pallet Width)</b>	50.00 in
<b>Dimensions - (Shipping Unit Depth)</b>	26.00 in

Attribute	Value
<b>Dimensions - (Shipping Unit Height)</b>	36.00 in
<b>Dimensions - (Shipping Unit Width)</b>	23.50 in
<b>Shipping Volume - (Unit)</b>	21996.000 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	21996.000 in <sup>3</sup>
<b>Weight - (Case)</b>	75.000 lb
<b>Weight - (Shipping Unit)</b>	75.000 lb
<b>Ecomm Path Display</b>	Equipment/Residential Split System/Coil