

# CMXV12AVJUA

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Multi-Split Fan Coil
<b>System Family</b>	Multi-Split
<b>Function Category</b>	Cooling Only
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Product Family</b>	CMXV_AVJUA
<b>Series Name</b>	Multi-Split Fan Coil Indoor
<b>Short Description</b>	Multi-Split Fan Coil Indoor Indoor Multi-Split Fan Coil
<b>Product Benefits</b>	12-year limited parts and compressor warranty with online registration;5-year limited parts warranty for commercial applications;Built in refrigeration detection system
<b>Product Features - (Standard)</b>	7 mm evaporator coil tube size;Variable-speed ECM blower motor;Compatible with Daikin One+ & Daikin One Touch Controls - No adaptors needed to wire controls;Constant CFM over wide range of static pressure conditions independent of duct system;All-Aluminum evaporator coil;Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193 ;Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRAE standard 193 ;3 kW – 10 kW electric heater kits ;Horizontal or vertical configuration capabilities;21" depth for easier attic access;DecaBDE-free thermoplastic drain pan with secondary drain connections ;Screw-less sides and back helps to reduce condensation when installed in humid locations
<b>Communication Feature</b>	Yes
<b>DOE Regional Compliance</b>	All
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Universal Product Code (UPC)</b>	663051950580
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	4
<b>Country of Origin</b>	USA

Attribute	Value
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>ProductDescriptionPIM</b>	R32 - Multi position Air Hander for Multi Zone - 1 Ton
<b>Producer</b>	Yes
<b>ProductIDBarcode</b>	CMXV12AVJUA
<b>MaxVoltage</b>	253 V
<b>MinVoltage</b>	197 V
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208-230 V
<b>AirFlowRateHighCooling</b>	400 ft <sup>3</sup> /min
<b>AirFlowRateHighHeating</b>	400 ft <sup>3</sup> /min
<b>AirFlowRateLowCooling</b>	280 ft <sup>3</sup> /min
<b>AirFlowRateLowHeating</b>	280 ft <sup>3</sup> /min
<b>AirFlowRateMediumCooling</b>	340 ft <sup>3</sup> /min
<b>AirFlowRateMediumHeating</b>	340 ft <sup>3</sup> /min
<b>AirFlowRateSuperLowCooling</b>	250 ft <sup>3</sup> /min
<b>AirFlowRateSuperLowHeating</b>	250 ft <sup>3</sup> /min
<b>CabinetFinish</b>	Galvanized, leather grain-embossed finish, Painted
<b>DimensionsBlowerDiameter</b>	10 in
<b>DimensionsBlowerWidth</b>	6 in
<b>DimensionsUnitDepth</b>	21 in
<b>DimensionsUnitHeight</b>	45 in
<b>DimensionsUnitWidth</b>	17.7 in
<b>HeatExchangerType</b>	Air Cooled
<b>NumberOfSpeeds</b>	Variable
<b>BlowerMotorHorsePower</b>	1/3 metric hp
<b>Tonnage</b>	1

Attribute	Value
<b>CondensateDrainOutlet</b>	3/4 in
<b>PipeSizeGas</b>	1/2 in
<b>PipeSizeLiquid</b>	1/4 in
<b>Proposition 65 Label</b>	Yes
<b>Carton Type</b>	CTN
<b>Case Qty</b>	1
<b>Dimensions - (Case Depth)</b>	24.50 in
<b>Dimensions - (Case Height)</b>	49.00 in
<b>Dimensions - (Case Width)</b>	18.50 in
<b>Dimensions - (Pallet Depth)</b>	49.00 in
<b>Dimensions - (Pallet Height)</b>	49.00 in
<b>Dimensions - (Pallet Width)</b>	37.50 in
<b>Dimensions - (Shipping Unit Depth)</b>	24.50 in
<b>Dimensions - (Shipping Unit Height)</b>	49.00 in
<b>Dimensions - (Shipping Unit Width)</b>	18.50 in
<b>Shipping Volume - (Unit)</b>	22209.250 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	22209.250 in <sup>3</sup>
<b>Weight - (Case)</b>	102.000 lb
<b>Weight - (Shipping Unit)</b>	102.000 lb
<b>Ecomm Path Display</b>	Equipment/Aftermarket Equipment/Aftermarket Air Conditioner
<b>Release Status</b>	Active