

# CMXV18AVJUA

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Multi-Split Fan Coil
<b>System Family</b>	Multi-Split
<b>Function Category</b>	Cooling Only
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Product Family</b>	CMXV_AVJUA
<b>Series Name</b>	Multi-Split Fan Coil Indoor
<b>Short Description</b>	Multi-Split Fan Coil Indoor Indoor Multi-Split Fan Coil
<b>Product Benefits</b>	12-year limited parts and compressor warranty with online registration;5-year limited parts warranty for commercial applications;Built in refrigeration detection system
<b>Product Features - (Standard)</b>	7 mm evaporator coil tube size;Variable-speed ECM blower motor;Compatible with Daikin One+ & Daikin One Touch Controls - No adaptors needed to wire controls;Constant CFM over wide range of static pressure conditions independent of duct system;All-Aluminum evaporator coil;Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193 ;Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRAE standard 193 ;3 kW – 10 kW electric heater kits ;Horizontal or vertical configuration capabilities;21" depth for easier attic access;DecaBDE-free thermoplastic drain pan with secondary drain connections ;Screw-less sides and back helps to reduce condensation when installed in humid locations
<b>Communication Feature</b>	Yes
<b>DOE Regional Compliance</b>	All
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Universal Product Code (UPC)</b>	663051950597
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	4
<b>Country of Origin</b>	USA

Attribute	Value
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	R32 - Multi position Air Hander for Multi Zone - 1.5 Ton
Producer	Yes
ProductIDBarcode	CMXV18AVJUA
MaxVoltage	253 V
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208-230 V
AirFlowRateHighCooling	600 ft³/min
AirFlowRateHighHeating	600 ft³/min
AirFlowRateLowCooling	420 ft³/min
AirFlowRateLowHeating	420 ft³/min
AirFlowRateMediumCooling	510 ft³/min
AirFlowRateMediumHeating	510 ft³/min
AirFlowRateSuperLowCooling	340 ft³/min
AirFlowRateSuperLowHeating	340 ft³/min
CabinetFinish	Galvanized, leather grain-embossed finish, Painted
DimensionsBlowerDiameter	10 in
DimensionsBlowerWidth	6 in
DimensionsUnitDepth	21 in
DimensionsUnitHeight	45 in
DimensionsUnitWidth	17.7 in
HeatExchangerType	Air Cooled
NumberOfSpeeds	Variable
BlowerMotorHorsePower	1/2 metric hp
Tonnage	1.5

Attribute	Value
<b>CondensateDrainOutlet</b>	3/4 in
<b>PipeSizeGas</b>	1/2 in
<b>PipeSizeLiquid</b>	1/4 in
<b>Proposition 65 Label</b>	Yes
<b>Carton Type</b>	CTN
<b>Case Qty</b>	1
<b>Dimensions - (Case Depth)</b>	24.50 in
<b>Dimensions - (Case Height)</b>	49.00 in
<b>Dimensions - (Case Width)</b>	18.50 in
<b>Dimensions - (Pallet Depth)</b>	49.00 in
<b>Dimensions - (Pallet Height)</b>	49.00 in
<b>Dimensions - (Pallet Width)</b>	37.50 in
<b>Dimensions - (Shipping Unit Depth)</b>	24.50 in
<b>Dimensions - (Shipping Unit Height)</b>	49.00 in
<b>Dimensions - (Shipping Unit Width)</b>	18.50 in
<b>Shipping Volume - (Unit)</b>	22209.250 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	22209.250 in <sup>3</sup>
<b>Weight - (Case)</b>	105.000 lb
<b>Weight - (Shipping Unit)</b>	105.000 lb
<b>Ecomm Path Display</b>	Equipment/Aftermarket Equipment/Aftermarket Air Conditioner
<b>Release Status</b>	Active