

# CMXV24AVJUA

| Attribute  | Value  |
|--|--|
| <b>Brand</b>   | Daikin   |
| <b>ProductCategory</b>                               | Ductless Mini-Splits   |
| <b>ProductClassPIM</b>                               | Multi-Split Fan Coil   |
| <b>System Family</b>                                 | Multi-Split  |
| <b>Function Category</b>                             | Cooling Only   |
| <b>Product Type</b>                                  | Equipment  |
| <b>Unit Type</b>                                     | Indoor   |
| <b>Product Family</b>                                | CMXV_AVJUA   |
| <b>Series Name</b>                                   | Multi-Split Fan Coil Indoor  |
| <b>Short Description</b>                             | Multi-Split Fan Coil Indoor Indoor Multi-Split Fan Coil  |
| <b>Product Benefits</b>                              | 12-year limited parts and compressor warranty with online registration;5-year limited parts warranty for commercial applications;Built in refrigeration detection system   |
| <b>Product Features - (Standard)</b>                 | 7 mm evaporator coil tube size;Variable-speed ECM blower motor;Compatible with Daikin One+ & Daikin One Touch Controls - No adaptors needed to wire controls;Constant CFM over wide range of static pressure conditions independent of duct system;All-Aluminum evaporator coil;Cabinet air leakage less than 2.0% at 1.0 inch H2O when tested in accordance with ASHRAE standard 193 ;Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRAE standard 193 ;3 kW – 10 kW electric heater kits ;Horizontal or vertical configuration capabilities;21" depth for easier attic access;DecaBDE-free thermoplastic drain pan with secondary drain connections ;Screw-less sides and back helps to reduce condensation when installed in humid locations |
| <b>Communication Feature</b>                         | Yes  |
| <b>DOE Regional Compliance</b>                       | All  |
| <b>Export Control Classification Number - (ECCN)</b> | EAR99  |
| <b>Universal Product Code (UPC)</b>                  | 663051950603   |
| <b>Item Stocking Unit of Measure (UOM)</b>           | EA   |
| <b>Pallet Qty</b>                                    | 4  |

| Attribute                  | Value  |
|----------------------------|--|
| Country of Origin          | USA  |
| US HTS Code                | 8415.90.8070   |
| Canadian HTS Code          | 8415.90.90.00  |
| ProductDescriptionPIM      | R32 - Multi position Air Hander for Multi Zone - 2.0 Ton |
| Producer                   | Yes  |
| ProductIDBarcode           | CMXV24AVJUA  |
| MaxVoltage                 | 253 V  |
| MinVoltage                 | 197 V  |
| PowerFrequency             | 60 Hz  |
| PowerPhase                 | 1 Ph   |
| PowerVoltage               | 208-230 V  |
| AirFlowRateHighCooling     | 800 ft <sup>3</sup> /min                                 |
| AirFlowRateHighHeating     | 800 ft <sup>3</sup> /min                                 |
| AirFlowRateLowCooling      | 560 ft <sup>3</sup> /min                                 |
| AirFlowRateLowHeating      | 560 ft <sup>3</sup> /min                                 |
| AirFlowRateMediumCooling   | 680 ft <sup>3</sup> /min                                 |
| AirFlowRateMediumHeating   | 680 ft <sup>3</sup> /min                                 |
| AirFlowRateSuperLowCooling | 450 ft <sup>3</sup> /min                                 |
| AirFlowRateSuperLowHeating | 450 ft <sup>3</sup> /min                                 |
| CabinetFinish              | Galvanized, leather grain-embossed finish, Painted       |
| DimensionsBlowerDiameter   | 10 in  |
| DimensionsBlowerWidth      | 6 in   |
| DimensionsUnitDepth        | 21 in  |
| DimensionsUnitHeight       | 45 in  |
| DimensionsUnitWidth        | 17.7 in  |
| HeatExchangerType          | Air Cooled   |
| NumberOfSpeeds             | Variable   |
| BlowerMotorHorsePower      | 1/2 metric hp  |

| Attribute                                  | Value   |
|--|---|
| <b>Tonnage</b>                             | 2   |
| <b>CondensateDrainOutlet</b>               | 3/4 in  |
| <b>PipeSizeGas</b>                         | 1/2 in  |
| <b>PipeSizeLiquid</b>                      | 1/4 in  |
| <b>Proposition 65 Label</b>                | Yes   |
| <b>Carton Type</b>                         | CTN   |
| <b>Case Qty</b>                            | 1   |
| <b>Dimensions - (Case Depth)</b>           | 24.50 in  |
| <b>Dimensions - (Case Height)</b>          | 49.00 in  |
| <b>Dimensions - (Case Width)</b>           | 18.50 in  |
| <b>Dimensions - (Pallet Depth)</b>         | 49.00 in  |
| <b>Dimensions - (Pallet Height)</b>        | 49.00 in  |
| <b>Dimensions - (Pallet Width)</b>         | 37.50 in  |
| <b>Dimensions - (Shipping Unit Depth)</b>  | 24.50 in  |
| <b>Dimensions - (Shipping Unit Height)</b> | 49.00 in  |
| <b>Dimensions - (Shipping Unit Width)</b>  | 18.50 in  |
| <b>Shipping Volume - (Unit)</b>            | 22209.250 in <sup>3</sup>                                   |
| <b>Truck Factor</b>                        | 0   |
| <b>Volume - (Case)</b>                     | 22209.250 in <sup>3</sup>                                   |
| <b>Weight - (Case)</b>                     | 108.000 lb  |
| <b>Weight - (Shipping Unit)</b>            | 108.000 lb  |
| <b>Ecomm Path Display</b>                  | Equipment/Aftermarket Equipment/Aftermarket Air Conditioner |
| <b>Release Status</b>                      | Active  |