

DC6TE09030

Attribute	Value
Brand	Daikin
ProductCategory	Light Commercial
ProductClassPIM	Light Commercial Split Air Conditioner
System Family	Light Commercial Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Light Commercial
Product Family	DC6TE_3
Series Name	DC6TE
Short Description	Light Commercial Split Air Conditioner
Product Features - (Standard)	Two-Stage tandem compressor design ;Quiet operating top discharge ;High-efficiency copper tube / aluminum fin coil ;Brass liquid and suction service valves ;High- and low-pressure switches ;Factory-installed filter drier ;Complies with ASHRAE 90.1 ;AHRI Certified; ETL Listed
Cabinet Features	Innovative sound control top design;Steel louver coil guard protects the coil from damage and adds strength to unit ;Bottom pan rails elevate unit above slab;Heavy-gauge galvanized-steel cabinet;Attractive Nickel Gray powder-paint finish;When properly anchored, meets the 2010 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)
Communication Feature	No
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051766006
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	16.4 IEER A/C R32, 7.5 Ton 208/230V 3PH

Attribute	Value
CoolingCapacityNominal	95000 Btu/H
EERDucted	12.3
EERHSVTC	12.3
ENERGYSTARCertified	No
IEERNonDucted	16.4
InstallationConfiguration	Top Discharge
Producer	Yes
ProductIDBarcode	DC6TE09030
CoolingOperationRangeStdMax	125 °F
CoolingOperationRangeStdMin	55 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
CompressorRLA	14.1 A
MaxOvercurrentProtection	50 A
MaxVoltage	253 V
MinCircuitAmps	38.7 A
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	3 Ph
PowerVoltage	208/230 V
RatedLoadAmps	14.1 A
CompressorStages	Two Stage
CompressorType	Scroll
DimensionsUnitDepth	35.5 in
DimensionsUnitHeight	41.5 in

Attribute	Value
DimensionsUnitWidth	35-1/2 in
MotorSpeedType	Single Speed
SoundPressureHighCooling	83.9 dBA
WeightUnit	381 lb
CoolingCapacityRated	95000 Btu/H
Tonnage	7.5
AdditionalRefrigerantCharge	1.54 lb
FactoryStdRefrigerantCharge	110 oz
LongLineSetLengthLinear	150 ft
MaxPipeLengthTotal	150 ft
MaxPipeLengthVertical	25 ft
PipeSizeGas	1-1/8 in
PipeSizeLiquid	5/8 in
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-32
ValveConnectionType	Sweat
ValveSizeLiquidOD	5/8 in
ValveSizeSuctionOD	1-1/8 in
VerticalLengthODAboveID	25 ft
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	44.00 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	44 in

Attribute	Value
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	44.00 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	44.00 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	60236 in ³
Shipping Volume - (Unit)	60236.000 in ³
Truck Factor	0
Volume - (Case)	60236.000 in ³
Volume - (Distribution Shipping Unit)	60236 in ³
Weight - (Case)	391.000 lb
Weight - (Distribution Shipping Unit)	391 lb
Weight - (Shipping Unit)	391.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Light Commercial Split System/Light Commercial Split Air Conditioner

Attribute	Value
Release Status	Active