

DX11TA1204

Attribute	Value
Brand	Daikin
ProductCategory	Light Commercial
ProductClassPIM	Light Commercial Split Air Conditioner
System Family	Light Commercial Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Light Commercial
Product Family	DX11TA_4
Short Description	Daikin Light Commercial Split Air Conditioner 11.2 EER/13.5 IEER, Two Stage, Three-Phase
Product Features - (Standard)	Two-Stage energy-efficient compressor; Quiet operating top discharge; High-efficiency copper tube / aluminum fin coil; Brass liquid and suction service valves; High and Low pressure switches; Factory installed filter drier; Complies with ASHRAE 90.1-2016; AHRI Certified; ETL Listed
Cabinet Features	Innovative sound control top design; Steel louver coil guard protects the coil from damage and adds strength to unit; 500-hour salt-spray tested; Bottom pan rails elevate unit above slab; Heavy-gauge galvanized steel cabinet; Attractive Nickel Gray powder paint finish; When properly anchored, meets the 2010 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available)
Export Control Classification Number - (ECCN)	1B999D
Universal Product Code (UPC)	663051566408
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
Long Description	Daikin Light Commercial Split Air Conditioner 11.2 EER/13.5 IEER, Two Stage, 10 Ton, Three-Phase
ProductDescriptionPIM	10 Ton AC, Two-Stage, 11.2 EER, 13.5 IEER, 460V 60Hz

Attribute	Value
AHRReferenceNumber	201990204
CoolingCapacityNominal	120000 Btu/H
EERDucted	11.2
EERHSVTC	11.2
IEERDucted	13.5
Producer	Yes
ProductIDBarcode	DX11TA1204
CoolingOperationRangeStdMax	115 °F
CoolingOperationRangeStdMin	65 °F
CoolingOperationRangewBaffleMin	55 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
CompressorLRA	130 A
CompressorRLA	14.8 A
MaxOvercurrentProtection	35 A
MaxVoltage	506 V
MinCircuitAmps	22.0 A
MinVoltage	414 V
OutdoorFLA	3.5 A
PowerFrequency	60 Hz
PowerPhase	3 Ph
PowerVoltage	460 V
RatedLoadAmps	12.0 A
ANSI	Yes
CompressorSoundBlanket	No

Attribute	Value
CompressorStages	Two Stage
CompressorType	Scroll
DimensionsUnitDepth	35-1/2 in
DimensionsUnitHeight	41-1/2 in
DimensionsUnitWidth	35-1/2 in
ETLListed	Yes
SoundPressureHighCooling	84 dBA
WeightUnit	340 lb
CondenserFanHorsepower	1 metric hp
CoolingCapacityRated	120000 Btu/H
CoolingCapacitySensible	80000 Btu/H
Tonnage	10
FactoryStdRefrigerantCharge	55 oz
IndoorTXVKit	TX5N4
LongLineSetLengthEquivalent	200 ft
LongLineSetLengthLinear	150 ft
MaxPipeLengthTotal	74 ft
MaxPipeLengthVertical	50 ft
PipeSizeGas	1-1/8 in
PipeSizeLiquid	5/8 in
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-410A
ValveConnectionType	Sweat
ValveSizeLiquidOD	5/8 in
ValveSizeSuctionOD	1-3/8 in
VerticalLengthODAboveID	25 ft
VerticalLengthODBelowID	80 ft
Proposition 65 Label	Yes

Attribute	Value
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	44.00 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	44 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	44.00 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	44.00 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	60236 in ³
Shipping Volume - (Unit)	60236.000 in ³
Truck Factor	0
Volume - (Case)	60236.000 in ³
Volume - (Distribution Shipping Unit)	60236 in ³
Weight - (Case)	340.000 lb
Weight - (Distribution Shipping Unit)	340 lb
Weight - (Shipping Unit)	340.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS

Attribute	Value
Registered Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Light Commercial Split System/Light Commercial Split Air Conditioner
Release Status	Hidden Sellable