

DX14XA0904

Attribute	Value
Brand	Daikin
ProductCategory	Light Commercial
ProductClassPIM	Light Commercial Split Air Conditioner
System Family	Light Commercial Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Light Commercial
Product Family	DX14X_4
Short Description	Light Commercial Split Air Conditioner
Product Features - (Standard)	Two-Stage energy efficient compressor ;Quiet operating top discharge;High-efficiency copper tube/aluminum fin coil ;Brass liquid and suction service valves ;factory installed filter drier;complies with ASHRAE 90.1;AHRI Certified; ETL Listed
Cabinet Features	Innovative sound control top design ;Steel Louver coil guard protects the coil from damage and adds strength to unit ;Bottom pan rails elevate unit above slab;Heavy-gauge galvanized steel cabinet ;attractive nickel gray powder-paint finish
Export Control Classification Number - (ECCN)	EAR99
ISO Certified	Yes
Universal Product Code (UPC)	663051671034
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	11.2 EER/15.2 IEER 7.5 TON AC 2-Stage 3-Phase 460V 60Hz
CoolingCapacityNominal	90000 Btu/H
Producer	Yes

Attribute	Value
ProductIDBarcode	DX14XA0904
CoolingOperationRangeStdMax	115 °F
CoolingOperationRangeStdMin	65 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
CompressorLRA	94 A
CompressorRLA	12.0 A
MaxOvercurrentProtection	30 A
MaxVoltage	506 V
MinCircuitAmps	18.5 A
MinVoltage	414 V
PowerFrequency	60 Hz
PowerPhase	3 Ph
PowerVoltage	460 V
CompressorStages	Two Stage
CompressorType	Scroll
DimensionsUnitDepth	35.5 in
DimensionsUnitHeight	41.5 in
DimensionsUnitWidth	35-1/2 in
SoundPressureHighCooling	83.7 dBA
FactoryStdRefrigerantCharge	55 oz
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-410A
ValveConnectionType	Sweat
ValveSizeLiquidOD	5/8 in

Attribute	Value
ValveSizeSuctionOD	1-3/8 in
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	44.00 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	44 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	44.00 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	44.00 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	60236 in ³
Shipping Volume - (Unit)	60236.000 in ³
Truck Factor	0
Volume - (Case)	60236.000 in ³
Volume - (Distribution Shipping Unit)	60236 in ³
Weight - (Case)	322.000 lb
Weight - (Distribution Shipping Unit)	322 lb
Weight - (Shipping Unit)	322.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS

Attribute	Value
Registered Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Light Commercial Split System/Light Commercial Split Air Conditioner
Release Status	Hidden Sellable