

# DX14XA1204

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Light Commercial
<b>ProductClassPIM</b>	Light Commercial Split Air Conditioner
<b>System Family</b>	Light Commercial Split System
<b>Function Category</b>	Cooling Only
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Outdoor
<b>Market Type</b>	Light Commercial
<b>Product Family</b>	DX14X_4
<b>Short Description</b>	Light Commercial Split Air Conditioner
<b>Product Features - (Standard)</b>	Two-Stage energy efficient compressor ;Quiet operating top discharge;High-efficiency copper tube/aluminum fin coil ;Brass liquid and suction service valves ;factory installed filter drier;complies with ASHRAE 90.1;AHRI Certified; ETL Listed
<b>Cabinet Features</b>	Innovative sound control top design ;Steel Louver coil guard protects the coil from damage and adds strength to unit ;Bottom pan rails elevate unit above slab;Heavy-gauge galvanized steel cabinet ;attractive nickel gray powder-paint finish
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>ISO Certified</b>	Yes
<b>Universal Product Code (UPC)</b>	663051671010
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	1
<b>Country of Origin</b>	USA
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>ProductDescriptionPIM</b>	11.2 EER/15.2 IEER 10 TON AC 2-Stage 3-Phase 460V 60Hz
<b>CoolingCapacityNominal</b>	115000 Btu/H
<b>Producer</b>	Yes

Attribute	Value
<b>ProductIDBarcode</b>	DX14XA1204
<b>CoolingOperationRangeStdMax</b>	115 °F
<b>CoolingOperationRangeStdMin</b>	65 °F
<b>RatedCoolingConditionAmbientDB</b>	95 °F
<b>RatedCoolingConditionAmbientWB</b>	75 °F
<b>RatedCoolingConditionRoomDB</b>	80 °F
<b>RatedCoolingConditionRoomWB</b>	67 °F
<b>CompressorLRA</b>	130 A
<b>CompressorRLA</b>	14.8 A
<b>MaxOvercurrentProtection</b>	35 A
<b>MaxVoltage</b>	506 V
<b>MinCircuitAmps</b>	22.0 A
<b>MinVoltage</b>	414 V
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	3 Ph
<b>PowerVoltage</b>	460 V
<b>CompressorStages</b>	Two Stage
<b>CompressorType</b>	Scroll
<b>DimensionsUnitDepth</b>	35.5 in
<b>DimensionsUnitHeight</b>	41.5 in
<b>DimensionsUnitWidth</b>	35-1/2 in
<b>SoundPressureHighCooling</b>	84.7 dBA
<b>FactoryStdRefrigerantCharge</b>	55 oz
<b>RefrigerantPreChargedLineLength</b>	15 ft
<b>RefrigerantType</b>	R-410A
<b>ValveConnectionType</b>	Sweat
<b>ValveSizeLiquidOD</b>	5/8 in

Attribute	Value
ValveSizeSuctionOD	1-3/8 in
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	44.00 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	44 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	44.00 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	44.00 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	60236 in <sup>3</sup>
Shipping Volume - (Unit)	60236.000 in <sup>3</sup>
Truck Factor	0
Volume - (Case)	60236.000 in <sup>3</sup>
Volume - (Distribution Shipping Unit)	60236 in <sup>3</sup>
Weight - (Case)	336.000 lb
Weight - (Distribution Shipping Unit)	336 lb
Weight - (Shipping Unit)	336.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS

Attribute	Value
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Light Commercial Split System/Light Commercial Split Air Conditioner
<b>Release Status</b>	Hidden Sellable