

DX3SEA4830

Attribute	Value
Brand	Daikin
ProductCategory	Light Commercial
ProductClassPIM	Light Commercial Split Air Conditioner
System Family	Light Commercial Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Light Commercial
Product Family	DX3SE_3
Series Name	DX3SE
Short Description	Light Commercial Split Air Conditioner
Product Benefits	Energy-efficient scroll compressor ;Copper tube/enhanced aluminum fin coil ;Factory-installed filter drier ;AHRI Certified
Product Features - (Standard)	Service valves with sweat connections and easy-access gauge ports. ;Copper tube/enhanced aluminum fin coil. ;Match systems have a minimum SEER2 rating of 13.4;Energy-efficient compressor;Contactor with lug connection
Cabinet Features	Innovative louvered sound control top design. ;Steel louver coil guard. ;Heavy-guage galvanized-steel cabinet.;Top and side maintenance access.;single-panel access to controls with space provided for field-installed accessories
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
ISO Certified	Yes
Universal Product Code (UPC)	663051682641
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00

Attribute	Value
ProductDescriptionPIM	13.4 SEER2 AC 208/230V 3PH, 4 TON
EER2HSVTC	11
SEER2HSVTC	13.4
InstallationConfiguration	Top Discharge
Producer	Yes
ProductIDBarcode	DX3SEA4830
CoolingOperationRangeStdMax	115 °F
CoolingOperationRangeStdMin	65 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
CompressorLRA	83.1 A
CompressorRLA	15.4 A
MaxOvercurrentProtection	30 A
MaxVoltage	253 V
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	3 Ph
PowerVoltage	208/230 V
CompressorStages	Single Stage
CompressorType	Scroll
DimensionsUnitDepth	35.5 in
DimensionsUnitHeight	35.75 in
DimensionsUnitWidth	35-1/2 in
MotorSpeedType	Single Speed
SoundPressureHighCooling	74 dBA

Attribute	Value
Tonnage	4
AdditionalRefrigerantCharge	0.6 lb
FactoryStdRefrigerantCharge	120 oz
MaxPipeLengthTotal	79 ft
MaxPipeLengthVertical	50 ft
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-410A
ValveConnectionType	Sweat
ValveSizeLiquidOD	3/8 in
ValveSizeSuctionOD	7/8 in
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	38.50 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	38.5 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	38.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	38.50 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	52706.5 in ³

Attribute	Value
Shipping Volume - (Unit)	52706.500 in ³
Truck Factor	0
Volume - (Case)	52706.500 in ³
Volume - (Distribution Shipping Unit)	52706.5 in ³
Weight - (Case)	231.000 lb
Weight - (Distribution Shipping Unit)	231 lb
Weight - (Shipping Unit)	231.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Light Commercial Split System/Light Commercial Split Air Conditioner
Release Status	Hidden Sellable