

DZ14XA1204

Attribute	Value
Brand	Daikin
ProductCategory	Light Commercial
ProductClassPIM	Light Commercial Split Heat Pump
System Family	Light Commercial Split System
Function Category	Heat Pump
Product Type	Equipment
Unit Type	Outdoor
Market Type	Light Commercial
Product Family	DZ14X_4
Short Description	Light Commercial Split Heat Pump
Product Features - (Standard)	Two-Stage energy efficient compressor ;High capacity steel cased bi -flow heat pump filter drier;Liquid refrigerant return protection. ;Reliable, Time-initiated, temperature terminated defrost control.;Brass liquid and suction line service valves mounted at a 90 degree angle with sweat connetions and sercice ports. ;High-Efficiency copper tube/aluminum fin coil ;Complies with ASHRAE 90.1-2019;AHRI Certified; ETL Listed
Cabinet Features	Innovative sound control top design ;Steel Louver coil guard protects the coil from damae and adds strength to unit ;Heavy-gauge galvanized steel cabinet ;Attractive nickel gray powder-paint finish
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
ISO Certified	Yes
Universal Product Code (UPC)	663051671058
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	11 EER/14.5 IEER 10 TON HP 2-Stage 3-Phase 460V 60Hz
InstallationConfiguration	Top Discharge

Attribute	Value
Producer	Yes
ProductIDBarcode	DZ14XA1204
CoolingOperationRangeStdMax	115 °F
CoolingOperationRangeStdMin	65 °F
HeatingOperationRangeStdMax	65 °F
HeatingOperationRangeStdMin	-5 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
RatedHeatingConditionAmbientDB	95 °F
RatedHeatingConditionAmbientWB	75 °F
RatedHeatingConditionRoomDB	80 °F
RatedHeatingConditionRoomWB	67 °F
CompressorLRA	130 A
CompressorRLA	14.8 A
MaxOvercurrentProtection	35 A
MaxVoltage	506 V
MinCircuitAmps	22.0 A
MinVoltage	414 V
PowerFrequency	60 Hz
PowerPhase	3 Ph
PowerVoltage	460 V
CompressorStages	Two Stage
CompressorType	Scroll
DimensionsUnitDepth	35.5 in

Attribute	Value
DimensionsUnitHeight	41.5 in
DimensionsUnitWidth	35-1/2 in
MotorSpeedType	Single Speed
SoundPressureHighCooling	84.4 dBA
Tonnage	10
FactoryStdRefrigerantCharge	55 oz
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-410A
ValveConnectionType	Sweat
ValveSizeLiquidOD	5/8 in
ValveSizeSuctionOD	1-3/8 in
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	44.00 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	44 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	44.00 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	44.00 in
Dimensions - (Shipping Unit Width)	37.00 in

Attribute	Value
Distribution Shipping Volume - (Unit)	60236 in ³
Shipping Volume - (Unit)	60236.000 in ³
Truck Factor	0
Volume - (Case)	60236.000 in ³
Volume - (Distribution Shipping Unit)	60236 in ³
Weight - (Case)	367.000 lb
Weight - (Distribution Shipping Unit)	367 lb
Weight - (Shipping Unit)	367.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Light Commercial Split System/Light Commercial Split Heat Pump
Release Status	Hidden Sellable