

# FBA24AAVJU

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Sky Air Fan Coil
<b>System Family</b>	Sky Air
<b>Function Category</b>	Heat Pump
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Light Commercial
<b>Product Family</b>	FBA_AAVJU
<b>Series Name</b>	FBA
<b>Short Description</b>	SkyAir Indoor Fan Coil
<b>Family Description</b>	HSP R-32 SkyAir 1.5 - 4.0 Ton DC Ducted Unit
<b>Product Benefits</b>	Up to 0.8" Static;Able to integrate with DZK;Economizer Control Logic;MERV 13 Filter Options
<b>Product Features - (Standard)</b>	10 Year parts and compressor Warrantly;DC Fan Motor;Minimal Discharge Air Temperature - mitigate risk of condensation;Auto Adjusting Airflow at commissioning based on external static pressure;Ease of Maintenance with complete service access from below;Built in Refrigerant Detection System with Dispersion Mode
<b>Communication Feature</b>	No
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	8
<b>Country of Origin</b>	Thailand
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>Long Description</b>	R-32 SkyAir Ducted Consealed Ceiling Unit
<b>ProductDescriptionPIM</b>	R-32 2.0 TON HSP DUCTED CONCEALED

Attribute	Value
AHRReferenceNumber	217175220
Producer	No
ProductIDBarcode	FBA24AAVJU
CurrentType	AC
FuseSize	15 A
InterConnectingWires	T1, T2
MaxOvercurrentProtection	15 A
MinCircuitAmps	1.9 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208-230 V
AirFlowRateHighCooling	742 ft <sup>3</sup> /min
AirFlowRateHighHeating	742 ft <sup>3</sup> /min
AirFlowRateLowCooling	565 ft <sup>3</sup> /min
AirFlowRateLowHeating	565 ft <sup>3</sup> /min
AirFlowRateMediumCooling	635 ft <sup>3</sup> /min
AirFlowRateMediumHeating	635 ft <sup>3</sup> /min
DimensionsUnitDepth	31-1/2 in
DimensionsUnitHeight	9-11/16 in
DimensionsUnitWidth	39-3/8 in
SoundPressureHighCooling	39 dBA
SoundPressureHighHeating	39 dBA
SoundPressureLowCooling	33 dBA
SoundPressureLowHeating	33 dBA
SoundPressureMediumCooling	35 dBA
SoundPressureMediumHeating	35 dBA
WeightUnit	84 lb
CoolingCapacityRated	24000 Btu/H

Attribute	Value
<b>CoolingCapacitySensible</b>	18700 Btu/H
<b>CoolingInputPower</b>	2.12 kW
<b>HeatingCapacityRated</b>	27000 Btu/H
<b>Tonnage</b>	2
<b>CondensateDrainOutlet</b>	1-1/4 in
<b>PipeSizeGas</b>	5/8 in
<b>PipeSizeLiquid</b>	3/8 in
<b>RefrigerantType</b>	R-32
<b>Proposition 65 Label</b>	Yes
<b>Carton Type</b>	CTN
<b>Case Qty</b>	1
<b>Dimensions - (Case Depth)</b>	47.50 in
<b>Dimensions - (Case Height)</b>	34.50 in
<b>Dimensions - (Case Width)</b>	11.50 in
<b>Dimensions - (Distribution Unit Depth)</b>	47.5 in
<b>Dimensions - (Distribution Unit Height)</b>	34.5 in
<b>Dimensions - (Distribution Unit Width)</b>	11.5 in
<b>Dimensions - (Pallet Depth)</b>	53.00 in
<b>Dimensions - (Pallet Height)</b>	74.00 in
<b>Dimensions - (Pallet Width)</b>	44.00 in
<b>Dimensions - (Shipping Unit Depth)</b>	47.50 in
<b>Dimensions - (Shipping Unit Height)</b>	34.50 in
<b>Dimensions - (Shipping Unit Width)</b>	11.50 in
<b>Distribution Shipping Volume - (Unit)</b>	18845.625 in <sup>3</sup>
<b>Shipping Volume - (Unit)</b>	18845.625 in <sup>3</sup>

Attribute	Value
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	18845.625 in <sup>3</sup>
<b>Volume - (Distribution Shipping Unit)</b>	18845.625 in <sup>3</sup>
<b>Weight - (Case)</b>	90.400 lb
<b>Weight - (Distribution Shipping Unit)</b>	90.4 lb
<b>Weight - (Shipping Unit)</b>	90.400 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 10 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 10 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 10 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 10 YEARS PARTS
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 10 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 10 YEARS PARTS
<b>Release Status</b>	Active