

FDMA24AVJU9

Attribute	Value
Brand	Daikin
ProductCategory	Ductless Mini-Splits
ProductClassPIM	Multi-Split Fan Coil
System Family	Multi-Split
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Indoor
Product Family	FDMA_AVJU9
Series Name	Multi-Split Fan Coil Indoor
Short Description	Multi-Split Fan Coil Indoor Indoor Multi-Split Fan Coil
Product Benefits	Inverter and PAM control technologies optimize energy use, delivering efficient performance and reduced electricity consumption;Concealed systems preserve interior aesthetics by eliminating bulky wall-mounted unit ideal for minimalist and design-focused homes;Concealed ducted mini splits offer zoned comfort with minimal ductwork, preserving the architectural integrity of historic homes;Concealed ducted systems efficiently condition large or multi-room spaces using flexible ductwork, offering seamless comfort without multiple wall units;Compact concealed systems deliver efficient, quiet comfort in small apartments without occupying valuable walls or floor space;Concealed systems maintain visual harmony by delivering discreet comfort without distracting from high-end displays or artwork.;Concealed systems deliver efficient climate control while preserving a clean,professional look free from exposed HVAC components;Concealed ducted mini-splits offer a space-saving, energy-efficient solution for individual climate control in apartments and condominiums;Concealed systems provide quiet, zoned climate control with advanced filtration—ideal for maintaining comfort and air quality in hospitals and hotels
Product Features - (Standard)	Auto Fan Speed;3-Step Switchable Fan speed;Quick Warming function;Program dry operation;Fan-only mode;ECONO operation;Titanium Apatite deodorizing filter;Filter Cleaning Indicator;Auto Restart after Power failure;Built in refrigeration detection system;Operation Range—Cooling (50°F - 114.8°F);Low temperature cooling operation down to -4°F (-20°C) with wind baffle and field settings;Operating Range - Heating (-13.8°F - 64.4°F);12-year limited parts and compressor warranty with online registration;5-year limited parts warranty for commercial applications
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051993402
Item Stocking Unit of Measure (UOM)	EA

Attribute	Value
Pallet Qty	8
Country of Origin	Thailand
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	R-32 2 Ton Ducted Concealed Indoor Unit
Producer	No
ProductIDBarcode	FDMA24AVJU9
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
RatedHeatingConditionAmbientDB	47 °F
RatedHeatingConditionAmbientWB	43 °F
RatedHeatingConditionRoomDB	70 °F
RatedHeatingConditionRoomWB	60 °F
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208-230 V
AirFlowRateHighCooling	666 ft ³ /min
AirFlowRateHighHeating	666 ft ³ /min
AirFlowRateLowCooling	426 ft ³ /min
AirFlowRateLowHeating	426 ft ³ /min
AirFlowRateMediumCooling	553 ft ³ /min
AirFlowRateMediumHeating	553 ft ³ /min
DimensionsUnitDepth	31-1/2 in
DimensionsUnitHeight	9-5/8 in

Attribute	Value
DimensionsUnitWidth	39-3/8 in
ExternalStaticPressureRated	0.6
HeatExchangerType	Air Cooled
SoundPressureHighCooling	40 dBA
SoundPressureHighHeating	40 dBA
WeightUnit	88 lb
CoolingCapacityRated	21800 Btu/H
CoolingCapacitySensible	15740 Btu/H
CoolingInputPower	2.21 kW
HeatingCapacityRated	24000 Btu/H
HeatingInputPower	2.79 kW
Tonnage	2
CondensateDrainOutlet	1 in
PipeSizeGas	5/8 in
PipeSizeLiquid	1/4 in
RatedHeightDifference	0 ft
RatedPipingLength	25 ft
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	47.00 in
Dimensions - (Case Height)	34.50 in
Dimensions - (Case Width)	11.50 in
Dimensions - (Pallet Depth)	53.00 in
Dimensions - (Pallet Height)	74.00 in
Dimensions - (Pallet Width)	44.00 in
Dimensions - (Shipping Unit Depth)	47.00 in

Attribute	Value
Dimensions - (Shipping Unit Height)	34.50 in
Dimensions - (Shipping Unit Width)	11.50 in
Shipping Volume - (Unit)	18647.250 in ³
Truck Factor	0
Volume - (Case)	18647.250 in ³
Weight - (Case)	88.000 lb
Weight - (Distribution Shipping Unit)	82 lb
Weight - (Shipping Unit)	88.000 lb
Ecomm Path Display	Equipment/Mini-Split/Mini-Split Heat Pump
Release Status	Active