

# FTA36AAVJUA

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Sky Air Fan Coil
<b>System Family</b>	Sky Air
<b>Function Category</b>	Heat Pump
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Light Commercial
<b>Product Family</b>	FTA_AAVJUA
<b>Series Name</b>	SkyAir FTA Multi Position Air Handler
<b>Short Description</b>	SkyAir Indoor Fan Coil
<b>Family Description</b>	R-32 1.5 - 4 Ton Inverter Multi Position Air Handler
<b>Product Benefits</b>	Upflow, downflow, horizontal right and horizontal left installation configurations;Wide line of 3W to 19W optional electric heat ;10 Year Parts and Compressor Warranty
<b>Product Features - (Standard)</b>	All Aluminum Coil;Less than 2% Air Leakage;External Static Pressure up to 0.9 in. w.g.;Optional Outside Air integration ;Factory integrated Refrigerant Leak Detection;Factory Installed Disconnect Option (D-Model);Anti Corrosion Treatment on Heat Exchanger
<b>Communication Feature</b>	No
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Universal Product Code (UPC)</b>	663051750180
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	4
<b>Country of Origin</b>	USA
<b>US HTS Code</b>	8415.90.8085
<b>Canadian HTS Code</b>	8415.90.90.00
<b>ProductDescriptionPIM</b>	Sky-Air R32 3.0 ton Multi-Position Air Handler

Attribute	Value
<b>InstallationConfiguration</b>	Upflow/Downflow/Horizontal
<b>Producer</b>	Yes
<b>ProductIDBarCode</b>	FTA36AAVJUA
<b>CurrentType</b>	AC
<b>FuseSize</b>	15 A
<b>InterConnectingWires</b>	F1, F2
<b>MaxOvercurrentProtection</b>	15 A
<b>MinCircuitAmps</b>	4.9 A
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208/230 V
<b>AirFlowRateHighCooling</b>	1050 ft <sup>3</sup> /min
<b>AirFlowRateHighHeating</b>	1050 ft <sup>3</sup> /min
<b>AirFlowRateLowCooling</b>	750 ft <sup>3</sup> /min
<b>AirFlowRateLowHeating</b>	750 ft <sup>3</sup> /min
<b>AirFlowRateMediumCooling</b>	900 ft <sup>3</sup> /min
<b>AirFlowRateMediumHeating</b>	900 ft <sup>3</sup> /min
<b>DimensionsUnitDepth</b>	21 in
<b>DimensionsUnitHeight</b>	45 in
<b>DimensionsUnitWidth</b>	17-1/2 in
<b>ExternalStaticPressureMax</b>	0.9
<b>MotorSpeedType</b>	Variable Speed
<b>SoundPressureHighCooling</b>	51.6 dBA
<b>SoundPressureHighHeating</b>	51.6 dBA
<b>SoundPressureLowCooling</b>	44 dBA
<b>SoundPressureLowHeating</b>	44 dBA
<b>SoundPressureMediumCooling</b>	48.2 dBA
<b>SoundPressureMediumHeating</b>	48.2 dBA

Attribute	Value
WeightUnit	118 lb
CoolingInputPower	3.5 kW
Tonnage	3
CondensateDrainOutlet	3/4 in
PipeSizeGas	5/8 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	23.00 in
Dimensions - (Case Height)	49.00 in
Dimensions - (Case Width)	18.50 in
Dimensions - (Distribution Unit Depth)	1 in
Dimensions - (Distribution Unit Height)	1 in
Dimensions - (Distribution Unit Width)	1 in
Dimensions - (Pallet Depth)	46.00 in
Dimensions - (Pallet Height)	49.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	23.00 in
Dimensions - (Shipping Unit Height)	49.00 in
Dimensions - (Shipping Unit Width)	18.50 in
Distribution Shipping Volume - (Unit)	1 in <sup>3</sup>
Shipping Volume - (Unit)	20849.500 in <sup>3</sup>
Truck Factor	0

Attribute	Value
Volume - (Case)	20849.500 in <sup>3</sup>
Volume - (Distribution Shipping Unit)	1 in <sup>3</sup>
Weight - (Case)	121.000 lb
Weight - (Distribution Shipping Unit)	1 lb
Weight - (Shipping Unit)	121.000 lb
Release Status	Active