

# FTXF09BVJU9

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Mini-Split Fan Coils
<b>System Family</b>	Mini-Split
<b>Function Category</b>	Heat Pump
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	FTXF_BVJU9
<b>Series Name</b>	Daikin OTERRA
<b>Short Description</b>	Series Indoor Mini-Split Fan Coils
<b>Family Description</b>	R-32 0.75 - 2.0 Ton Wall Mounted Unit Heat Pump
<b>Product Benefits</b>	R-32 Easy, Proven, Efficient, Available;Inverter Technology reduces energy cost;Uniform air circulation;Optimal comfort;quiet operations;clean and purified indoor air;easy to clean;worry free operation
<b>Product Features - (Standard)</b>	Wi-Fi built in on OTERRA Indoor Unit;Inverter;Power airflow dual flaps;Wide angle Louvers;Verticle Auto Swing (up and Down);Auto Fan Speed;Quiet operation;Auto Defrosting;Automatic Operation;Programme Dry Function;Fan only Mode;Sleep mode;R/C with backlight &Signal; receiving sign;Catechin filter/Green Tea Filter;Titanium Apatite Air Purifying filter;wipe clean flat panel;Auto Restart (after power failure);Self Daignosis
<b>Installation Type</b>	Wall Mounted
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	8
<b>Country of Origin</b>	Mexico
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>ProductDescriptionPIM</b>	R-32 --- 0.75- Ton, Heat Pump, Wall Mounted IDU Daikin OTERRA
<b>ENERGYSTARCertified</b>	Yes

Attribute	Value
<b>Producer</b>	No
<b>ProductIDBarcode</b>	FTXF09BVJU9
<b>CoolingOperationRangeStdMax</b>	118.4 °F
<b>CoolingOperationRangeStdMin</b>	50 °F
<b>HeatingOperationRangeStdMax</b>	64.4 °F
<b>HeatingOperationRangeStdMin</b>	5 °F
<b>RatedCoolingConditionAmbientDB</b>	95 °F
<b>RatedCoolingConditionAmbientWB</b>	75 °F
<b>RatedCoolingConditionRoomDB</b>	80 °F
<b>RatedCoolingConditionRoomWB</b>	67 °F
<b>RatedHeatingConditionAmbientDB</b>	47 °F
<b>RatedHeatingConditionAmbientWB</b>	43 °F
<b>RatedHeatingConditionRoomDB</b>	70 °F
<b>RatedHeatingConditionRoomWB</b>	60 °F
<b>CurrentType</b>	AC
<b>InterConnectingWires</b>	L1, L2, L3 Ground
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208-230 V
<b>AirFlowRateHighCooling</b>	381 ft <sup>3</sup> /min
<b>AirFlowRateHighHeating</b>	385 ft <sup>3</sup> /min
<b>AirFlowRateLowCooling</b>	230 ft <sup>3</sup> /min
<b>AirFlowRateLowHeating</b>	230 ft <sup>3</sup> /min
<b>AirFlowRateMediumCooling</b>	272 ft <sup>3</sup> /min
<b>AirFlowRateMediumHeating</b>	304 ft <sup>3</sup> /min
<b>AirFlowRateSuperLowCooling</b>	124 ft <sup>3</sup> /min

Attribute	Value
AirFlowRateSuperLowHeating	194 ft <sup>3</sup> /min
DimensionsUnitDepth	8-3/4 in
DimensionsUnitHeight	11-1/4 in
DimensionsUnitWidth	30-5/8 in
HeatExchangerType	Air Cooled
MaxOutdoorUnits	1
SoundPressureHighCooling	44 dBA
SoundPressureHighHeating	41 dBA
SoundPressureLowCooling	30 dBA
SoundPressureLowHeating	28 dBA
SoundPressureMediumCooling	35 dBA
SoundPressureMediumHeating	35 dBA
SoundPressureSuperLowCooling	19 dBA
SoundPressureSuperLowHeating	25 dBA
WeightUnit	19 lb
CoolingCapacityRated	9000 Btu/H
CoolingCapacitySensible	8250 Btu/H
HeatingCapacityRated	10900 Btu/H
Tonnage	0.75
CondensateDrainOutlet	5/8 in
PipeSizeGas	3/8 in
PipeSizeLiquid	1/4 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	33.50 in
Dimensions - (Case Height)	12.50 in

Attribute	Value
<b>Dimensions - (Case Width)</b>	15.00 in
<b>Dimensions - (Distribution Unit Depth)</b>	33.5 in
<b>Dimensions - (Distribution Unit Height)</b>	12.5 in
<b>Dimensions - (Distribution Unit Width)</b>	15 in
<b>Dimensions - (Pallet Depth)</b>	48.00 in
<b>Dimensions - (Pallet Height)</b>	30.00 in
<b>Dimensions - (Pallet Width)</b>	45.00 in
<b>Dimensions - (Shipping Unit Depth)</b>	33.50 in
<b>Dimensions - (Shipping Unit Height)</b>	12.50 in
<b>Dimensions - (Shipping Unit Width)</b>	15.00 in
<b>Distribution Shipping Volume - (Unit)</b>	6281.25 in <sup>3</sup>
<b>Shipping Volume - (Unit)</b>	6281.250 in <sup>3</sup>
<b>Truck Factor</b>	0
<b>Volume - (Case)</b>	6281.250 in <sup>3</sup>
<b>Volume - (Distribution Shipping Unit)</b>	6281.25 in <sup>3</sup>
<b>Weight - (Case)</b>	25.000 lb
<b>Weight - (Distribution Shipping Unit)</b>	25 lb
<b>Weight - (Shipping Unit)</b>	25.000 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 12 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 12 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS

Attribute	Value
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Mini-Split/Mini-Split Fan Coils
<b>Release Status</b>	Active