

FTXF12BVJU9

Attribute	Value
Brand	Daikin
ProductCategory	Ductless Mini-Splits
ProductClassPIM	Mini-Split Fan Coils
System Family	Mini-Split
Function Category	Heat Pump
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	FTXF_BVJU9
Series Name	Daikin OTERRA
Short Description	Series Indoor Mini-Split Fan Coils
Family Description	R-32 0.75 - 2.0 Ton Wall Mounted Unit Heat Pump
Product Benefits	R-32 Easy, Proven, Efficient, Available;Inverter Technology reduces energy cost;Uniform air circulation;Optimal comfort;quiet operations;clean and purified indoor air;easy to clean;worry free operation
Product Features - (Standard)	Wi-Fi built in on OTERRA Indoor Unit;Inverter;Power airflow dual flaps;Wide angle Louvers;Verticle Auto Swing (up and Down);Auto Fan Speed;Quiet operation;Auto Defrosting;Automatic Operation;Programme Dry Function;Fan only Mode;Sleep mode;R/C with backlight &Signal; receiving sign;Catechin filter/Green Tea Filter;Titanium Apatite Air Purifying filter;wipe clean flat panel;Auto Restart (after power failure);Self Daignosis
Installation Type	Wall Mounted
Export Control Classification Number - (ECCN)	EAR99
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	8
Country of Origin	Mexico
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
ProductDescriptionPIM	R-32 --- 1- Ton, Heat Pump, Wall Mounted IDU Daikin OTERRA
ENERGYSTARCertified	Yes

Attribute	Value
Producer	No
ProductIDBarcode	FTXF12BVJU9
CoolingOperationRangeStdMax	118.4 °F
CoolingOperationRangeStdMin	50 °F
HeatingOperationRangeStdMax	64.4 °F
HeatingOperationRangeStdMin	5 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
RatedHeatingConditionAmbientDB	47 °F
RatedHeatingConditionAmbientWB	43 °F
RatedHeatingConditionRoomDB	70 °F
RatedHeatingConditionRoomWB	60 °F
CurrentType	AC
InterConnectingWires	L1, L2, L3 Ground
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208-230 V
AirFlowRateHighCooling	399 ft ³ /min
AirFlowRateHighHeating	438 ft ³ /min
AirFlowRateLowCooling	219 ft ³ /min
AirFlowRateLowHeating	240 ft ³ /min
AirFlowRateMediumCooling	282 ft ³ /min
AirFlowRateMediumHeating	318 ft ³ /min
AirFlowRateSuperLowCooling	117 ft ³ /min

Attribute	Value
AirFlowRateSuperLowHeating	205 ft ³ /min
DimensionsUnitDepth	8-3/4 in
DimensionsUnitHeight	11-1/4 in
DimensionsUnitWidth	30-5/8 in
HeatExchangerType	Air Cooled
MaxOutdoorUnits	1
SoundPressureHighCooling	46 dBA
SoundPressureHighHeating	45 dBA
SoundPressureLowCooling	31 dBA
SoundPressureLowHeating	30 dBA
SoundPressureMediumCooling	37 dBA
SoundPressureMediumHeating	37 dBA
SoundPressureSuperLowCooling	19 dBA
SoundPressureSuperLowHeating	25 dBA
WeightUnit	19 lb
CoolingCapacityRated	12000 Btu/H
CoolingCapacitySensible	9880 Btu/H
HeatingCapacityRated	13500 Btu/H
Tonnage	1
CondensateDrainOutlet	5/8 in
PipeSizeGas	3/8 in
PipeSizeLiquid	1/4 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	33.50 in
Dimensions - (Case Height)	12.50 in

Attribute	Value
Dimensions - (Case Width)	15.00 in
Dimensions - (Distribution Unit Depth)	33.5 in
Dimensions - (Distribution Unit Height)	12.5 in
Dimensions - (Distribution Unit Width)	15 in
Dimensions - (Pallet Depth)	48.00 in
Dimensions - (Pallet Height)	30.00 in
Dimensions - (Pallet Width)	45.00 in
Dimensions - (Shipping Unit Depth)	33.50 in
Dimensions - (Shipping Unit Height)	12.50 in
Dimensions - (Shipping Unit Width)	15.00 in
Distribution Shipping Volume - (Unit)	6281.25 in ³
Shipping Volume - (Unit)	6281.250 in ³
Truck Factor	0
Volume - (Case)	6281.250 in ³
Volume - (Distribution Shipping Unit)	6281.25 in ³
Weight - (Case)	25.000 lb
Weight - (Distribution Shipping Unit)	25 lb
Weight - (Shipping Unit)	25.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 12 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 12 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS

Attribute	Value
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Mini-Split/Mini-Split Fan Coils
Release Status	Active