

# FTXF24AXVJU

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Mini-Split Fan Coils
<b>System Family</b>	Mini-Split
<b>Function Category</b>	Heat Pump
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Indoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	FTXF_AXVJU
<b>Series Name</b>	Daikin OTERRA
<b>Short Description</b>	Series Indoor Mini-Split Fan Coils
<b>Family Description</b>	R-32 --- 0.75 - 2.0 Ton Wall Mounted Unit Heat Pump
<b>Product Benefits</b>	R-32 Easy, Proven, Efficient, Available;Inverter Technology Reduces Energy Cost;Uniform Air Circualtion;Optimal Comfort;Quiet Operations;Clean and Purified Indoor Air;Easy to Clean;Worry Free operation
<b>Product Features - (Standard)</b>	Inverter;Power-airflow Dual Flaps;Wide Angle Louvers;Vericle Auto-Swing (Up and Down);Auto Fan Speed;Quiet Operation;Auto Defrosting;Automatic Operation;Programme Dry Function;Fan Only Mode;Sleep mode;R/C with backlight & Signal Receiving Sign;Catechin Filter/Green Tea Filter;Titanium Apatite Air-Purifying Filter;Wipe Clean Flat Panel;Auto Restart (after power failure);Self-Diagnosis
<b>Communication Feature</b>	No
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	12
<b>Country of Origin</b>	Malaysia
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>ProductDescriptionPIM</b>	R-32 --- 2- Ton, Heat Pump, Wall Mounted IDU Daikin OTERRA
<b>AHRReferenceNumber</b>	213895722

Attribute	Value
<b>ENERGYSTARCertified</b>	Yes
<b>Producer</b>	No
<b>ProductIDBarcode</b>	FTXF24AXVJU
<b>CoolingOperationRangeStdMax</b>	122 °F
<b>CoolingOperationRangeStdMin</b>	50 °F
<b>HeatingOperationRangeStdMax</b>	64.4 °F
<b>HeatingOperationRangeStdMin</b>	5 °F
<b>RatedCoolingConditionAmbientDB</b>	95 °F
<b>RatedCoolingConditionAmbientWB</b>	75 °F
<b>RatedCoolingConditionRoomDB</b>	80 °F
<b>RatedCoolingConditionRoomWB</b>	67 °F
<b>RatedHeatingConditionAmbientDB</b>	47 °F
<b>RatedHeatingConditionAmbientWB</b>	43 °F
<b>RatedHeatingConditionRoomDB</b>	70 °F
<b>RatedHeatingConditionRoomWB</b>	60 °F
<b>CurrentType</b>	AC
<b>FanMotorOutput</b>	39
<b>IndoorFLA</b>	0.17 A
<b>InterConnectingWires</b>	L1, L2, L3, Ground
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208-230 V
<b>AirFlowRateHighCooling</b>	716 ft <sup>3</sup> /min
<b>AirFlowRateHighHeating</b>	716 ft <sup>3</sup> /min
<b>AirFlowRateLowCooling</b>	467 ft <sup>3</sup> /min
<b>AirFlowRateLowHeating</b>	467 ft <sup>3</sup> /min

Attribute	Value
<b>AirFlowRateMediumCooling</b>	605 ft <sup>3</sup> /min
<b>AirFlowRateMediumHeating</b>	605 ft <sup>3</sup> /min
<b>AirFlowRateSuperHighCooling</b>	754 ft <sup>3</sup> /min
<b>AirFlowRateSuperHighHeating</b>	754 ft <sup>3</sup> /min
<b>AirFlowRateSuperLowCooling</b>	395 ft <sup>3</sup> /min
<b>AirFlowRateSuperLowHeating</b>	395 ft <sup>3</sup> /min
<b>DimensionsUnitDepth</b>	10-3/4 in
<b>DimensionsUnitHeight</b>	11-11/16 in
<b>DimensionsUnitWidth</b>	39-9/16 in
<b>HeatExchangerType</b>	Air Cooled
<b>MoistureRemovalRate</b>	0.88
<b>SoundPressureHighCooling</b>	53 dBA
<b>SoundPressureHighHeating</b>	53 dBA
<b>SoundPressureLowCooling</b>	39 dBA
<b>SoundPressureLowHeating</b>	38 dBA
<b>SoundPressureMediumCooling</b>	45 dBA
<b>SoundPressureMediumHeating</b>	43 dBA
<b>SoundPressureSuperLowCooling</b>	34 dBA
<b>SoundPressureSuperLowHeating</b>	34 dBA
<b>WeightUnit</b>	30.5 lb
<b>CoolingCapacityRated</b>	22400 Btu/H
<b>CoolingCapacitySensible</b>	24000 Btu/H
<b>CoolingInputPower</b>	6.57 kW
<b>HeatingCapacityRated</b>	23600 Btu/H
<b>HeatingInputPower</b>	6.92 kW
<b>Tonnage</b>	2
<b>CondensateDrainOutlet</b>	5/8 in
<b>MaxPipeLengthTotal</b>	98.5 ft

Attribute	Value
PipeSizeGas	5/8 in
PipeSizeLiquid	1/4 in
RatedHeightDifference	0 ft
RatedPipingLength	25 ft
RefrigerantPreChargedLineLength	33 ft
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	14.50 in
Dimensions - (Case Height)	14.50 in
Dimensions - (Case Width)	42.00 in
Dimensions - (Distribution Unit Depth)	14.5 in
Dimensions - (Distribution Unit Height)	14.5 in
Dimensions - (Distribution Unit Width)	42 in
Dimensions - (Pallet Depth)	62.00 in
Dimensions - (Pallet Height)	48.50 in
Dimensions - (Pallet Width)	42.00 in
Dimensions - (Shipping Unit Depth)	14.50 in
Dimensions - (Shipping Unit Height)	14.50 in
Dimensions - (Shipping Unit Width)	42.00 in
Distribution Shipping Volume - (Unit)	8830.5 in <sup>3</sup>
Shipping Volume - (Unit)	8830.500 in <sup>3</sup>
Truck Factor	0
Volume - (Case)	8830.500 in <sup>3</sup>

Attribute	Value
<b>Volume - (Distribution Shipping Unit)</b>	8830.5 in <sup>3</sup>
<b>Weight - (Case)</b>	36.000 lb
<b>Weight - (Distribution Shipping Unit)</b>	36 lb
<b>Weight - (Shipping Unit)</b>	36.000 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 12 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 12 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Mini-Split/Mini-Split Fan Coils
<b>Release Status</b>	Obsolete