

# FTXV09AVJU9

| Attribute                                     | Value  |
|---|--|
| Brand   | Daikin   |
| ProductCategory                               | Ductless Mini-Splits   |
| ProductClassPIM                               | Multi-Split Fan Coil   |
| System Family                                 | Multi-Split  |
| Function Category                             | Cooling Only   |
| Product Type                                  | Equipment  |
| Unit Type                                     | Indoor   |
| Market Type                                   | Residential-Single Family  |
| Product Family                                | FTXV_AVJU9   |
| Series Name                                   | Multi-Split Fan Coil Indoor  |
| Short Description                             | Multi-Split Fan Coil Indoor Indoor Multi-Split Fan Coil  |
| Family Description                            | R-32 0.75 - 2.0 Ton Wall Mounted Unit  |
| Product Benefits                              | Quiet operation ;Low ambient cooling operation down to -4°F (-20°C) with field setting and air adjustment grille;Operating Range - Cooling (50°F - 114.8°F);Operating Range - Heating (-13°F - 64.4°F);12 year limited parts and compressor warranty with online registration;5 year limited parts warranty for commercial applications;Factory Installed Wi-Fi module - Simple App Set up |
| Product Features - (Standard)                 | 12 Year limited Warranty for Parts and Compressor;Sound pressure as low as 19 dB(A);Washable Dry Filter;Powerful Operation mode;Auto fan speed control;Quick warming function  |
| Installation Type                             | Wall Mounted   |
| Communication Feature                         | Yes  |
| Export Control Classification Number - (ECCN) | EAR99  |
| Item Stocking Unit of Measure (UOM)           | EA   |
| Pallet Qty                                    | 8  |
| Country of Origin                             | Mexico   |
| US HTS Code                                   | 8415.90.8070   |
| Canadian HTS Code                             | 8415.90.90.00  |
| ProductDescriptionPIM                         | 3/4 Ton Wall Mount R-32  |

| Attribute                             | Value                    |
|---------------------------------------|--------------------------|
| <b>Producer</b>                       | No                       |
| <b>ProductIDBarcode</b>               | FTXV09AVJU9              |
| <b>RatedCoolingConditionAmbientDB</b> | 95 °F                    |
| <b>RatedCoolingConditionAmbientWB</b> | 75 °F                    |
| <b>RatedCoolingConditionRoomDB</b>    | 80 °F                    |
| <b>RatedCoolingConditionRoomWB</b>    | 67 °F                    |
| <b>RatedHeatingConditionAmbientDB</b> | 47 °F                    |
| <b>RatedHeatingConditionAmbientWB</b> | 43 °F                    |
| <b>RatedHeatingConditionRoomDB</b>    | 70 °F                    |
| <b>RatedHeatingConditionRoomWB</b>    | 60 °F                    |
| <b>InterConnectingWires</b>           | L1, L2, L3, G            |
| <b>PowerFrequency</b>                 | 60 Hz                    |
| <b>PowerPhase</b>                     | 1 Ph                     |
| <b>PowerVoltage</b>                   | 208-230 V                |
| <b>AirFlowRateHighCooling</b>         | 381 ft <sup>3</sup> /min |
| <b>AirFlowRateHighHeating</b>         | 385 ft <sup>3</sup> /min |
| <b>AirFlowRateLowCooling</b>          | 230 ft <sup>3</sup> /min |
| <b>AirFlowRateLowHeating</b>          | 230 ft <sup>3</sup> /min |
| <b>AirFlowRateMediumCooling</b>       | 272 ft <sup>3</sup> /min |
| <b>AirFlowRateMediumHeating</b>       | 304 ft <sup>3</sup> /min |
| <b>AirFlowRateSuperLowCooling</b>     | 166 ft <sup>3</sup> /min |
| <b>AirFlowRateSuperLowHeating</b>     | 194 ft <sup>3</sup> /min |
| <b>DimensionsUnitDepth</b>            | 8-3/4 in                 |
| <b>DimensionsUnitHeight</b>           | 11-1/4 in                |
| <b>DimensionsUnitWidth</b>            | 30-5/16 in               |
| <b>HeatExchangerType</b>              | Air Cooled               |

| Attribute                               | Value    |
|---|----------|
| SoundPressureHighCooling                | 43 dBA   |
| SoundPressureHighHeating                | 41 dBA   |
| SoundPressureLowCooling                 | 31 dBA   |
| SoundPressureLowHeating                 | 28 dBA   |
| SoundPressureMediumCooling              | 35 dBA   |
| SoundPressureMediumHeating              | 35 dBA   |
| SoundPressureSuperLowCooling            | 24 dBA   |
| SoundPressureSuperLowHeating            | 25 dBA   |
| WeightUnit                              | 19 lb    |
| Tonnage                                 | 0.75     |
| CondensateDrainOutlet                   | 5/8 in   |
| PipeSizeGas                             | 3/8 in   |
| PipeSizeLiquid                          | 1/4 in   |
| RatedHeightDifference                   | 0 ft     |
| RefrigerantType                         | R-32     |
| Proposition 65 Label                    | Yes      |
| Carton Type                             | CTN      |
| Case Qty                                | 1        |
| Dimensions - (Case Depth)               | 33.00 in |
| Dimensions - (Case Height)              | 12.50 in |
| Dimensions - (Case Width)               | 14.50 in |
| Dimensions - (Distribution Unit Depth)  | 33 in    |
| Dimensions - (Distribution Unit Height) | 12.5 in  |
| Dimensions - (Distribution Unit Width)  | 14.5 in  |
| Dimensions - (Pallet Depth)             | 48.00 in |
| Dimensions - (Pallet Height)            | 30.00 in |
| Dimensions - (Pallet Width)             | 45.00 in |

| Attribute                                       | Value                                      |
|---|--|
| <b>Dimensions - (Shipping Unit Depth)</b>       | 33.00 in                                   |
| <b>Dimensions - (Shipping Unit Height)</b>      | 12.50 in                                   |
| <b>Dimensions - (Shipping Unit Width)</b>       | 14.50 in                                   |
| <b>Distribution Shipping Volume - (Unit)</b>    | 5981.25 in <sup>3</sup>                    |
| <b>Shipping Volume - (Unit)</b>                 | 5981.000 in <sup>3</sup>                   |
| <b>Truck Factor</b>                             | 0  |
| <b>Volume - (Case)</b>                          | 5981.000 in <sup>3</sup>                   |
| <b>Volume - (Distribution Shipping Unit)</b>    | 5981.25 in <sup>3</sup>                    |
| <b>Weight - (Case)</b>                          | 25.000 lb                                  |
| <b>Weight - (Distribution Shipping Unit)</b>    | 25 lb                                      |
| <b>Weight - (Shipping Unit)</b>                 | 25.000 lb                                  |
| <b>Registered Parts Warranty - Commercial</b>   | ALL PARTS - 5 YEARS PARTS                  |
| <b>Registered Parts Warranty - Multi-Family</b> | ALL PARTS - 12 YEARS PARTS                 |
| <b>Registered Parts Warranty - Residential</b>  | ALL PARTS - 12 YEARS PARTS                 |
| <b>Standard Parts Warranty - Commercial</b>     | ALL PARTS - 5 YEARS PARTS                  |
| <b>Standard Parts Warranty - Multi-Family</b>   | ALL PARTS - 5 YEARS PARTS                  |
| <b>Standard Parts Warranty - Residential</b>    | ALL PARTS - 5 YEARS PARTS                  |
| <b>Ecomm Path Display</b>                       | Equipment/Multi-Split/Multi-Split Fan Coil |
| <b>Release Status</b>                           | Active                                     |