

# FVXS18WVJU9

| Attribute  | Value   |
|--|---|
| <b>Brand</b>   | Daikin  |
| <b>ProductCategory</b>                               | Ductless Mini-Splits  |
| <b>ProductClassPIM</b>                               | Multi-Split Fan Coil  |
| <b>System Family</b>                                 | Multi-Split   |
| <b>Function Category</b>                             | Cooling Only  |
| <b>Product Type</b>                                  | Equipment   |
| <b>Unit Type</b>                                     | Indoor  |
| <b>Market Type</b>                                   | Residential-Single Family   |
| <b>Product Family</b>                                | FVXS_WVJU9  |
| <b>Series Name</b>                                   | FVXS  |
| <b>Short Description</b>                             | Multi-Split Fan Coil Indoor Indoor Multi-Split Fan Coil   |
| <b>Family Description</b>                            | 0.75 - 1.5 Ton Floor Standing Unit  |
| <b>Product Benefits</b>                              | 12 limited warranty for Part and Compressor;Titanium Apatite deodorizing filter;Wipe-clean cabinet;5 step switchable fan speeds   |
| <b>Product Features - (Standard)</b>                 | Stylish Cabinet can be resessed into wall;Dual direction for Airflow - Top for Cooling and Bottom for Heating;Quiet indoor operation;Hot Start during heating to eliminate cold air cirulation;Powerful operation to help reach set point quickly on startup;Econo operation to optimize comfort wth energy savings |
| <b>Installation Type</b>                             | Floor Standing  |
| <b>Export Control Classification Number - (ECCN)</b> | EAR99   |
| <b>Item Stocking Unit of Measure (UOM)</b>           | EA  |
| <b>Pallet Qty</b>                                    | 12  |
| <b>Country of Origin</b>                             | Japan   |
| <b>US HTS Code</b>                                   | 8415.90.8070  |
| <b>Canadian HTS Code</b>                             | 8415.90.90.00   |
| <b>ProductDescriptionPIM</b>                         | 1-1/2 Ton Floor Mount   |
| <b>Producer</b>                                      | No  |
| <b>ProductIDBarCode</b>                              | FVXS18WVJU9   |

| Attribute                             | Value                                 |
|---------------------------------------|---------------------------------------|
| <b>RatedCoolingConditionAmbientDB</b> | 95 °F                                 |
| <b>RatedCoolingConditionAmbientWB</b> | 75 °F                                 |
| <b>RatedCoolingConditionRoomDB</b>    | 80 °F                                 |
| <b>RatedCoolingConditionRoomWB</b>    | 67 °F                                 |
| <b>RatedHeatingConditionAmbientDB</b> | 47 °F                                 |
| <b>RatedHeatingConditionAmbientWB</b> | 43 °F                                 |
| <b>RatedHeatingConditionRoomDB</b>    | 70 °F                                 |
| <b>RatedHeatingConditionRoomWB</b>    | 60 °F                                 |
| <b>InterConnectingWires</b>           | See Outdoor Unit for Electrical Specs |
| <b>PowerFrequency</b>                 | 60 Hz                                 |
| <b>PowerPhase</b>                     | 1 Ph                                  |
| <b>PowerVoltage</b>                   | 208-230 V                             |
| <b>AirFlowRateHighCooling</b>         | 378 ft <sup>3</sup> /min              |
| <b>AirFlowRateHighHeating</b>         | 417 ft <sup>3</sup> /min              |
| <b>AirFlowRateLowCooling</b>          | 275 ft <sup>3</sup> /min              |
| <b>AirFlowRateLowHeating</b>          | 300 ft <sup>3</sup> /min              |
| <b>AirFlowRateMediumCooling</b>       | 325 ft <sup>3</sup> /min              |
| <b>AirFlowRateMediumHeating</b>       | 357 ft <sup>3</sup> /min              |
| <b>AirFlowRateSuperLowCooling</b>     | 233 ft <sup>3</sup> /min              |
| <b>AirFlowRateSuperLowHeating</b>     | 251 ft <sup>3</sup> /min              |
| <b>DimensionsUnitDepth</b>            | 8-1/4 in                              |
| <b>DimensionsUnitHeight</b>           | 23-5/8 in                             |
| <b>DimensionsUnitWidth</b>            | 27-9/16 in                            |
| <b>HeatExchangerType</b>              | Air Cooled                            |
| <b>SoundPressureHighCooling</b>       | 44 dBA                                |
| <b>SoundPressureHighHeating</b>       | 45 dBA                                |

| Attribute                               | Value    |
|---|----------|
| SoundPressureLowCooling                 | 36 dBA   |
| SoundPressureLowHeating                 | 36 dBA   |
| SoundPressureMediumCooling              | 40 dBA   |
| SoundPressureMediumHeating              | 40 dBA   |
| SoundPressureSuperLowCooling            | 32 dBA   |
| SoundPressureSuperLowHeating            | 32 dBA   |
| WeightUnit                              | 31 lb    |
| Tonnage                                 | 1.25     |
| PipeSizeGas                             | 1/2 in   |
| PipeSizeLiquid                          | 1/4 in   |
| RatedHeightDifference                   | 0 ft     |
| RatedPipingLength                       | 25 ft    |
| RefrigerantType                         | R-410A   |
| Proposition 65 Label                    | Yes      |
| Carton Type                             | CTN      |
| Case Qty                                | 1        |
| Dimensions - (Case Depth)               | 31.00 in |
| Dimensions - (Case Height)              | 27.00 in |
| Dimensions - (Case Width)               | 11.00 in |
| Dimensions - (Distribution Unit Depth)  | 31 in    |
| Dimensions - (Distribution Unit Height) | 27 in    |
| Dimensions - (Distribution Unit Width)  | 11 in    |
| Dimensions - (Pallet Depth)             | 48.00 in |
| Dimensions - (Pallet Height)            | 86.00 in |
| Dimensions - (Pallet Width)             | 40.00 in |
| Dimensions - (Shipping Unit Depth)      | 31.00 in |

| Attribute                                       | Value                                      |
|---|--|
| <b>Dimensions - (Shipping Unit Height)</b>      | 27.00 in                                   |
| <b>Dimensions - (Shipping Unit Width)</b>       | 11.00 in                                   |
| <b>Distribution Shipping Volume - (Unit)</b>    | 9207 in <sup>3</sup>                       |
| <b>Shipping Volume - (Unit)</b>                 | 9207.000 in <sup>3</sup>                   |
| <b>Truck Factor</b>                             | 0  |
| <b>Volume - (Case)</b>                          | 9207.000 in <sup>3</sup>                   |
| <b>Volume - (Distribution Shipping Unit)</b>    | 9207 in <sup>3</sup>                       |
| <b>Weight - (Case)</b>                          | 38.000 lb                                  |
| <b>Weight - (Distribution Shipping Unit)</b>    | 38 lb                                      |
| <b>Weight - (Shipping Unit)</b>                 | 38.000 lb                                  |
| <b>Registered Parts Warranty - Commercial</b>   | ALL PARTS - 5 YEARS PARTS                  |
| <b>Registered Parts Warranty - Multi-Family</b> | ALL PARTS - 12 YEARS PARTS                 |
| <b>Registered Parts Warranty - Residential</b>  | ALL PARTS - 12 YEARS PARTS                 |
| <b>Standard Parts Warranty - Commercial</b>     | ALL PARTS - 5 YEARS PARTS                  |
| <b>Standard Parts Warranty - Multi-Family</b>   | ALL PARTS - 5 YEARS PARTS                  |
| <b>Standard Parts Warranty - Residential</b>    | ALL PARTS - 5 YEARS PARTS                  |
| <b>Ecomm Path Display</b>                       | Equipment/Multi-Split/Multi-Split Fan Coil |
| <b>Release Status</b>                           | Obsolete                                   |