

MBVK20DP0X00

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Air Handler
System Family	Unitary Split System
Function Category	Air Handler
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	MBVK
Series Name	Modular Blower
Short Description	Modular Blower Air Handler, Variable Speed ECM Motor, 5 Ton
Product Features - (Standard)	1. Variable-speed ECM blower motor;Compatible with Daikin One+ smart thermostat and other Daikin communicating equipment;3. Advanced configuration of the airflow and tonnage in communicating mode;4. Provides constant CFM over a wide range of static pressure conditions independent of duct system;5. CFM indicator;6. Fault recall of six most recent faults;7. Provides adjustable low CFM for efficient fan-only operation;8. Improved humidity and comfort control;9. Built-in compatibility with multi-stage heat pump and cooling applications;10. Blower section usable as electric heater;11. AHRI certified;12. ETL listed;13. Compatible with both R410A and R32 (use Intergration Kit)
Cabinet Features	1. Horizontal or vertical configuration capabilities;2. 21" depth for easier attic access;3. Foil-faced insulation covers the internal casing to reduce cabinet condensation;4. Galvanized, leather grain-embossed finish;5. Cabinet air leakage less than 2% at 1.0 inch H2O when tested in accordance with ASHRE standard 193;6. Cabinet air leakage less than 1.4% at 0.5 inch H2O when tested in accordance with ASHRE standard 193
Installation Type	Ducted
Communication Feature	Yes
Communication Feature Type	Daikin One+ Smart Thermostat compatible
Export Control Classification Number - (ECCN)	EAR99
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	8
Country of Origin	Mexico

Attribute	Value
US HTS Code	8414.59.6560
Canadian HTS Code	8414.59.00.92
Long Description	Modular Blower Ducted Air Handler, Variable Speed ECM Motor, 3.55 Ton, 27 in Cabinet with N/A Expansion, Daikin One+ Smart Thermostat compatible
CoolingCapacityNominal	0 Btu/H
InstallationConfiguration	Up-flow, Counterflow and Horizontal
Producer	No
ProductIDBarcode	MBVK20DP0X00
IndoorFLA	8.3 A
MaxOvercurrentProtection	15 A
MaxVoltage	126 V
MinCircuitAmps	10.4 A
MinVoltage	103 V
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
BlowerMotorRPM	2000 r/min
DimensionsBlowerDiameter	11 in
DimensionsBlowerWidth	10 in
DimensionsUnitDepth	21 in
DimensionsUnitHeight	30 in
DimensionsUnitWidth	27 in
EvapMotorRPM	1250 r/min
ExpansionDevice	N/A
IndoorOrificeSize	0 in
MotorSpeedType	Variable Speed ECM
WeightUnit	86 lb
BlowerMotorHorsePower	0.75 metric hp
Tonnage	5

Attribute	Value
TonnageRange	3.5;5
CondensateDrainOutlet	0 in
FactoryStdRefrigerantCharge	0 oz
PipeSizeGas	0 in
PipeSizeLiquid	0 in
RefrigerantType	N/A
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	26.00 in
Dimensions - (Case Height)	32.50 in
Dimensions - (Case Width)	26.00 in
Dimensions - (Distribution Unit Depth)	26 in
Dimensions - (Distribution Unit Height)	32.5 in
Dimensions - (Distribution Unit Width)	26 in
Dimensions - (Pallet Depth)	55.00 in
Dimensions - (Pallet Height)	69.50 in
Dimensions - (Pallet Width)	54.00 in
Dimensions - (Shipping Unit Depth)	26.00 in
Dimensions - (Shipping Unit Height)	32.50 in
Dimensions - (Shipping Unit Width)	26.00 in
Shipping Volume - (Unit)	21970.000 in ³
Truck Factor	0
Volume - (Case)	21970.000 in ³
Volume - (Distribution Shipping Unit)	21970 in ³

Attribute	Value
Weight - (Case)	86.090 lb
Weight - (Distribution Shipping Unit)	86.09 lb
Weight - (Shipping Unit)	86.090 lb