

RXQ09ASBU9

Attribute	Value
Brand	Daikin
ProductCategory	Ductless Mini-Splits
ProductClassPIM	Mini-Split Heat Pump
System Family	Mini-Split
Function Category	Heat Pump
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	RXQ_ASBU9
Series Name	Daikin Oterra 115V
Short Description	Series Outdoor Mini-Split Heat Pump, Single Zone
Model Efficiency	20 SEER
Family Description	0.75-1 Ton Daikin Oterra 115V Heat Pump
Product Benefits	Quiet Outdoor Unit;Long Compressor Life;Saves on Energy cost;Efficient operation
Product Features - (Standard)	Swing Compressor;Inverter system;Reluctance DC Motor;PAM Control;Automatic Defrosting;Anticorrosion treatment on Heat Exchanger
Communication Feature	No
Export Control Classification Number - (ECCN)	EAR99
Item Stocking Unit of Measure (UOM)	1
Pallet Qty	8
Country of Origin	Mexico
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
Long Description	Outdoor Mini-Split Heat Pump, & HSPF, Single Zone,
ProductDescriptionPIM	Daikin Oterra 115V Heat Pump Ductless ODU 0.75 Ton
ENERGYSTARCertified	No

Attribute	Value
Producer	No
ProductIDBarcode	RXQ09ASBU9
CoolingOperationRangeStdMax	114.8 °F
CoolingOperationRangeStdMin	50 °F
HeatingOperationRangeStdMax	65 °F
HeatingOperationRangeStdMin	5 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
RatedHeatingConditionAmbientDB	47 °F
RatedHeatingConditionAmbientWB	43 °F
RatedHeatingConditionRoomDB	70 °F
RatedHeatingConditionRoomWB	60 °F
CurrentType	AC
Fan/CompressorDriveInput	11.3 A
FuseSize	15 A
InterConnectingWires	4
MaxOvercurrentProtection	15 A
MinCircuitAmps	14.9 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
AirFlowRateHighCooling	1233 ft ³ /min
AirFlowRateHighHeating	1151 ft ³ /min
CompressorStages	Inverter

Attribute	Value
CompressorType	Swing
DimensionsUnitDepth	11-3/16 in
DimensionsUnitHeight	21-15/16 in
DimensionsUnitWidth	26-9/16 in
ETLListed	Yes
ExpansionDevice	EEV
HeatExchangerType	Air Cooled
MaxIndoorUnits	1
SoundPressureHighCooling	48 dBA
SoundPressureHighHeating	49 dBA
WeightUnit	59 lb
CoolingCapacityMax	10500 Btu/H
CoolingCapacityMin	2800 Btu/H
CoolingCapacityRated	9000 Btu/H
HeatingCapacityMax	12000 Btu/H
HeatingCapacityMin	3800 Btu/H
HeatingCapacityRated	10900 Btu/H
Tonnage	0.75
AdditionalRefrigerantCharge	0.22 lb
CondensateDrainOutlet	5/8 in
FactoryStdRefrigerantCharge	1.15 oz
MaxPipeLengthTotal	66 ft
MaxPipeLengthVertical	50 ft
PipeSizeGas	3/8 in
PipeSizeLiquid	1/4 in
RatedHeightDifference	50 ft
RatedPipingLength	50 ft
RefrigerantPreChargedLineLength	50 ft

Attribute	Value
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	31.50 in
Dimensions - (Case Height)	24.00 in
Dimensions - (Case Width)	14.00 in
Dimensions - (Distribution Unit Depth)	31.5 in
Dimensions - (Distribution Unit Height)	24 in
Dimensions - (Distribution Unit Width)	14 in
Dimensions - (Pallet Depth)	48.00 in
Dimensions - (Pallet Height)	53.50 in
Dimensions - (Pallet Width)	45.00 in
Dimensions - (Shipping Unit Depth)	31.50 in
Dimensions - (Shipping Unit Height)	24.00 in
Dimensions - (Shipping Unit Width)	14.00 in
Distribution Shipping Volume - (Unit)	10584 in ³
Shipping Volume - (Unit)	10584.000 in ³
Truck Factor	0
Volume - (Case)	10584.000 in ³
Volume - (Distribution Shipping Unit)	10584 in ³
Weight - (Case)	64.000 lb
Weight - (Distribution Shipping Unit)	64 lb
Weight - (Shipping Unit)	64.000 lb

Attribute	Value
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 12 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Mini-Split/Mini-Split Heat Pump
Release Status	Active