

# RXT12AVJU9

Attribute	Value
<b>Brand</b>	Daikin
<b>ProductCategory</b>	Ductless Mini-Splits
<b>ProductClassPIM</b>	Mini-Split Heat Pump
<b>System Family</b>	Mini-Split
<b>Function Category</b>	Heat Pump
<b>Product Type</b>	Equipment
<b>Unit Type</b>	Outdoor
<b>Market Type</b>	Residential-Single Family
<b>Product Family</b>	RXT_AVJU9
<b>Series Name</b>	AURORA
<b>Short Description</b>	Series Outdoor Mini-Split Heat Pump, Single Zone
<b>Family Description</b>	0.75 - 2.0 Ton AURORA R-32 Split Heat Pump Up to 21.0 SEER2 / 10.5 HSPF2 / 12.2 EER2
<b>Product Benefits</b>	12 Year Registered Residential Warranty;5 Year Commercial Warranty;Cooling 50-115F;Heating -13-60F
<b>Product Features - (Standard)</b>	Swing Inverter Compressor;Extended Operating Range and Capacity;Automatic Defrost
<b>Communication Feature</b>	Yes
<b>DOE Regional Compliance</b>	North;Southeast;Southwest
<b>Export Control Classification Number - (ECCN)</b>	EAR99
<b>Item Stocking Unit of Measure (UOM)</b>	EA
<b>Pallet Qty</b>	8
<b>Country of Origin</b>	Mexico
<b>US HTS Code</b>	8415.90.8070
<b>Canadian HTS Code</b>	8415.90.90.00
<b>Long Description</b>	Outdoor Mini-Split Heat Pump, & HSPF, Single Zone,
<b>ProductDescriptionPIM</b>	20.0 SEER2, Heat Pump, Ductless ODU, 1.0 Ton, Daikin AURORA R-32

Attribute	Value
<b>ENERGYSTARCertified</b>	Yes
<b>Producer</b>	No
<b>ProductIDBarcode</b>	RXT12AVJU9
<b>CoolingOperationRangeStdMax</b>	115 °F
<b>CoolingOperationRangeStdMin</b>	50 °F
<b>CoolingOperationRangewBaffleMin</b>	-4 °F
<b>HeatingOperationRangeStdMax</b>	60 °F
<b>HeatingOperationRangeStdMin</b>	-13 °F
<b>RatedCoolingConditionAmbientDB</b>	95 °F
<b>RatedCoolingConditionAmbientWB</b>	75 °F
<b>RatedCoolingConditionRoomDB</b>	80 °F
<b>RatedCoolingConditionRoomWB</b>	67 °F
<b>RatedHeatingConditionAmbientDB</b>	47 °F
<b>RatedHeatingConditionAmbientWB</b>	43 °F
<b>RatedHeatingConditionRoomDB</b>	70 °F
<b>RatedHeatingConditionRoomWB</b>	60 °F
<b>CurrentType</b>	AC
<b>Fan/CompressorDriveInput</b>	0.17 A
<b>FuseSize</b>	15 A
<b>InterConnectingWires</b>	L1, L2, L3, G
<b>MaxOvercurrentProtection</b>	15 A
<b>MinCircuitAmps</b>	14.6 A
<b>PowerFrequency</b>	60 Hz
<b>PowerPhase</b>	1 Ph
<b>PowerVoltage</b>	208-230 V
<b>AirFlowRateHighCooling</b>	1088 ft <sup>3</sup> /min

Attribute	Value
AirFlowRateHighHeating	1126 ft <sup>3</sup> /min
CompressorStages	Inverter
CompressorType	Swing
DimensionsUnitDepth	11-3/16 in
DimensionsUnitHeight	21-15/16 in
DimensionsUnitWidth	26-6/16 in
ExpansionDevice	EEV
HeatExchangerType	Air Cooled
MaxIndoorUnits	1
SoundPressureHighCooling	50 dBA
SoundPressureHighHeating	52 dBA
WeightUnit	72 lb
CoolingCapacityMax	14600 Btu/H
CoolingCapacityMin	4400 Btu/H
CoolingCapacityRated	10600 Btu/H
HeatingCapacityMax	18800 Btu/H
HeatingCapacityMin	4400 Btu/H
HeatingCapacityRated	13500 Btu/H
Tonnage	1
AdditionalRefrigerantCharge	0.22 lb
CondensateDrainOutlet	5/8 in
FactoryStdRefrigerantCharge	1.74 oz
MaxPipeLengthTotal	66 ft
MaxPipeLengthVertical	49.25 ft
PipeSizeGas	3/8 in
PipeSizeLiquid	1/4 in
RatedHeightDifference	0 ft
RatedPipingLength	25 ft

Attribute	Value
RefrigerantOil	PVE (FVC50K)
RefrigerantPreChargedLineLength	49.25 ft
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	31.50 in
Dimensions - (Case Height)	24.00 in
Dimensions - (Case Width)	14.00 in
Dimensions - (Distribution Unit Depth)	31.5 in
Dimensions - (Distribution Unit Height)	24 in
Dimensions - (Distribution Unit Width)	14 in
Dimensions - (Pallet Depth)	48.00 in
Dimensions - (Pallet Height)	53.50 in
Dimensions - (Pallet Width)	45.00 in
Dimensions - (Shipping Unit Depth)	31.50 in
Dimensions - (Shipping Unit Height)	24.00 in
Dimensions - (Shipping Unit Width)	14.00 in
Distribution Shipping Volume - (Unit)	10584 in <sup>3</sup>
Shipping Volume - (Unit)	10584.000 in <sup>3</sup>
Truck Factor	0
Volume - (Case)	10584.000 in <sup>3</sup>
Volume - (Distribution Shipping Unit)	10584 in <sup>3</sup>
Weight - (Case)	77.000 lb

Attribute	Value
<b>Weight - (Distribution Shipping Unit)</b>	77 lb
<b>Weight - (Shipping Unit)</b>	77.000 lb
<b>Registered Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Registered Parts Warranty - Multi-Family</b>	ALL PARTS - 12 YEARS PARTS
<b>Registered Parts Warranty - Residential</b>	ALL PARTS - 12 YEARS PARTS
<b>Standard Parts Warranty - Commercial</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Multi-Family</b>	ALL PARTS - 5 YEARS PARTS
<b>Standard Parts Warranty - Residential</b>	ALL PARTS - 5 YEARS PARTS
<b>Ecomm Path Display</b>	Equipment/Mini-Split/Mini-Split Heat Pump
<b>Release Status</b>	Active