

RXT15AVJU9

Attribute	Value
Brand	Daikin
ProductCategory	Ductless Mini-Splits
ProductClassPIM	Mini-Split Heat Pump
System Family	Mini-Split
Function Category	Heat Pump
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	RXT_AVJU9
Series Name	AURORA
Short Description	Series Outdoor Mini-Split Heat Pump, Single Zone
Family Description	0.75 - 2.0 Ton AURORA R-32 Split Heat Pump Up to 21.0 SEER2 / 10.5 HSPF2 / 12.2 EER2
Product Benefits	12 Year Registered Residential Warranty;5 Year Commercial Warranty;Cooling 50-115F;Heating -13-60F
Product Features - (Standard)	Swing Inverter Compressor;Extended Operating Range and Capacity;Automatic Defrost
Communication Feature	Yes
DOE Regional Compliance	North;Southeast;Southwest
Export Control Classification Number - (ECCN)	EAR99
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	8
Country of Origin	Mexico
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
Long Description	Outdoor Mini-Split Heat Pump, & HSPF, Single Zone,
ProductDescriptionPIM	21.0 SEER2, Heat Pump, Ductless ODU, 1.25 Ton, Daikin AURORA R-32

Attribute	Value
AHRReferenceNumber	216618814
ENERGYSTARCertified	Yes
Producer	No
ProductIDBarcode	RXT15AVJU9
CoolingOperationRangeStdMax	115 °F
CoolingOperationRangeStdMin	50 °F
CoolingOperationRangewBaffleMin	-4 °F
HeatingOperationRangeStdMax	60 °F
HeatingOperationRangeStdMin	-13 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
RatedHeatingConditionAmbientDB	47 °F
RatedHeatingConditionAmbientWB	43 °F
RatedHeatingConditionRoomDB	70 °F
RatedHeatingConditionRoomWB	60 °F
CurrentType	AC
Fan/CompressorDriveInput	0.38 A
FuseSize	20 A
InterConnectingWires	L1, L2, L3, G
MaxOvercurrentProtection	20 A
MinCircuitAmps	16.0 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208-230 V

Attribute	Value
AirFlowRateHighCooling	2097 ft ³ /min
AirFlowRateHighHeating	2327 ft ³ /min
CompressorStages	Inverter
CompressorType	Swing
DimensionsUnitDepth	12-5/8 in
DimensionsUnitHeight	29-1/2 in
DimensionsUnitWidth	31-1/4 in
ETLListed	Yes
ExpansionDevice	EEV
HeatExchangerType	Air Cooled
MaxIndoorUnits	1
SoundPressureHighCooling	52 dBA
SoundPressureHighHeating	57 dBA
WeightUnit	113 lb
CoolingCapacityMax	18400 Btu/H
CoolingCapacityMin	5800 Btu/H
CoolingCapacityRated	15000 Btu/H
HeatingCapacityMax	24600 Btu/H
HeatingCapacityMin	5800 Btu/H
HeatingCapacityRated	18300 Btu/H
Tonnage	1.25
AdditionalRefrigerantCharge	0.22 lb
CondensateDrainOutlet	5/8 in
FactoryStdRefrigerantCharge	2.45 oz
MaxPipeLengthTotal	98.5 ft
MaxPipeLengthVertical	66 ft
PipeSizeGas	1/2 in
PipeSizeLiquid	1/4 in

Attribute	Value
RatedHeightDifference	0 ft
RatedPipingLength	25 ft
RefrigerantPreChargedLineLength	49.25 ft
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	40.00 in
Dimensions - (Case Height)	32.00 in
Dimensions - (Case Width)	16.00 in
Dimensions - (Distribution Unit Depth)	40 in
Dimensions - (Distribution Unit Height)	32 in
Dimensions - (Distribution Unit Width)	16 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	69.00 in
Dimensions - (Pallet Width)	48.00 in
Dimensions - (Shipping Unit Depth)	40.00 in
Dimensions - (Shipping Unit Height)	32.00 in
Dimensions - (Shipping Unit Width)	16.00 in
Distribution Shipping Volume - (Unit)	20480 in ³
Shipping Volume - (Unit)	20480.000 in ³
Truck Factor	0
Volume - (Case)	20480.000 in ³
Volume - (Distribution Shipping Unit)	20480 in ³

Attribute	Value
Weight - (Case)	121.000 lb
Weight - (Distribution Shipping Unit)	121 lb
Weight - (Shipping Unit)	121.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 12 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 12 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Mini-Split/Mini-Split Heat Pump
Release Status	Active