



60A FUSIBLE DISCONNECT SWITCH

Item#: **DDS-60**

This DiversiTech® DDS-60 Fusible Disconnect Switch, 60 Amps fused model designed with fuses in pull out handle for easy replacement. The line, load, and ground terminals are aligned for ease of wiring. This product has a reversible door. The side open door opens more than 180 degrees for maximum access and has a full dead front. The UL Listed number is IRF9, NEMA Type 3R and the US Patent is 6,630,637.

Product Features & Benefits

- Constructed for outdoor use, it is rain tight, High Temperature and sleet resistant.
- The line, load, and ground terminals are aligned for ease of wiring.
- Reversible door which opens to either left or right, High Temperature and also opens more than 180° for maximum access and has a full dead front

- Fused model designed with fuses in pull-out handle for easy replacement.

Specifications

▲

Includes	N/A
Power Supply	Single Phase
Application	HVAC/R
cUL Listed	Yes
Max Volts (V)	240
UL Listed	Yes
Amps	60
Disconnect Mechanism	Pull-Out Handle
Fused / Non-Fused	Non-Fusible
NEMA Rating	3R (Rain & Sleet Resistant)
No. of Fuses	2
Top or Side Open	Side

Order Info

▲

UPC	0095247082452
Primary UoM	Each
Primary Depth (inches)	3
Primary Width (inches)	5.25
Primary Height (inches)	8.63
Primary Weight (lbs)	3.1
Quick Ship Flag	Yes
Order Multiple	10