

# AMVT30BP1300

Generated from workbook row data

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Air Handler
System Family	Unitary Split System
Function Category	Air Handler
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	AMVT_32
Series Name	R-32 AMVT
Short Description	R-32 AMVT Air Handler, Variable Speed Motor, Ton
Product Benefits	<ol style="list-style-type: none"> <li>1. Internal factory-installed thermal expansion valves for cooling and heat pump applications</li> <li>2. Variable-speed ECM blower motor</li> <li>3. Integrated communicating ComfortBridge™ Technology</li> <li>4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud phone and tablet application</li> <li>5. Auto configuration of the airflow and tonnage in communicating mode</li> <li>6. Provides constant CFM over a wide range of static pressure conditions independent of duct system</li> <li>7. CFM indicator</li> <li>8. Fault recall of six most recent faults</li> <li>9. Provides adjustable low CFM for efficient fan-only operation</li> <li>10. Improved humidity and comfort control</li> <li>11. Built-in compatibility with multi-stage heat pump and cooling applications</li> <li>12. All-aluminum evaporator coil</li> <li>13. AHRI certified</li> <li>ETL listed</li> <li>14. Rigid SmartFrame™ cabinet</li> <li>15. Horizontal or vertical configuration capabilities</li> <li>16. DecaBDE-free thermoplastic drain pan with secondary drain connections</li> <li>17. Foil-faced insulation covers the internal casing to reduce cabinet condensation</li> <li>18. Field Installed 3 kW – 25 kW electric heater kits available</li> </ol>

Attribute	Value
Product Features - (Standard)	<ol style="list-style-type: none"> <li>1. Internal factory-installed thermal expansion valves for cooling and heat pump applications</li> <li>2. Variable-speed ECM blower motor</li> <li>3. Integrated communicating ComfortBridge Technology</li> <li>4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud phone and tablet application.</li> <li>5. Auto configuration of the airflow and tonnage in communicating mode</li> <li>6. Provides constant CFM over a wide range of static pressure conditions independent of duct system</li> <li>7. CFM indicator</li> <li>8. Fault recall of six most recent faults</li> <li>9. Provides adjustable low CFM for efficient fan-only operation</li> <li>10. Improved humidity and comfort control</li> <li>11. Built-in compatibility with multi-stage heat pump and cooling applications</li> <li>12. Optimized for R-32 refrigerant with factory installed leak detection sensor for A2L mitigation.</li> </ol>
Cabinet Features	<ol style="list-style-type: none"> <li>1. Rigid SmartFrame™ cabinet</li> <li>2. Cabinet air leakage less than 2.0% at 1.0 inch H<sub>2</sub>O when tested in accordance with ASHRAE standard 193</li> <li>3. Cabinet air leakage less than 1.4% at 0.5 inch H<sub>2</sub>O when tested in accordance with ASHRAE standard 193</li> <li>4. Horizontal or vertical configuration capabilities</li> <li>5. 21" depth for easier attic access</li> <li>6. DecaBDE-free thermoplastic drain pan with secondary drain connections</li> <li>7. Screw-less sides and back helps to reduce condensation when installed in humid locations</li> <li>8. Foil-faced insulation covers the internal casing to reduce cabinet condensation</li> <li>9. Galvanized, leather grain-embossed finish</li> <li>10 .Glue-less cabinet insulation retention</li> </ol>
Installation Type	Ducted Multi-position
Communication Feature	No
Communication Feature Type	ComfortBridge Technology compatible
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051736375
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	USA
US HTS Code	8415.90.8085
Canadian HTS Code	8415.90.90.00
Long Description	R-32 AMVT Ducted Multi-position Air Handler, Variable Speed Motor, 2.5 Ton, 17-9/16 in Cabinet with TXV Expansion, ComfortBridge Technology compatible
ProductDescriptionPIM	air handler
CoolingCapacityNominal	30000 Btu/H
Producer	Yes

Attribute	Value
ProductIDBarcode	AMVT30BP1300
IndoorFLA	3.9 A
MaxOvercurrentProtection	50/60 A
MaxVoltage	253 V
MinCircuitAmps	4.9/4.9 A
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208/240 V
DimensionsBlowerDiameter	10 in
DimensionsBlowerWidth	6 in
DimensionsUnitDepth	21 in
DimensionsUnitHeight	53-7/16 in
DimensionsUnitWidth	17-9/16 in
ExpansionDevice	TXV
MotorSpeedType	Variable Speed
WeightUnit	134 lb
BlowerMotorHorsePower	0.5 metric hp
TonnageRange	2.5
FactoryStdRefrigerantCharge	0.5 oz
PipeSizeGas	3/4 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	24.50 in
Dimensions - (Case Height)	57.50 in
Dimensions - (Case Width)	18.50 in
Dimensions - (Distribution Unit Depth)	24.5 in
Dimensions - (Distribution Unit Height)	57.5 in
Dimensions - (Distribution Unit Width)	18.5 in

Attribute	Value
Dimensions - (Pallet Depth)	49.00 in
Dimensions - (Pallet Height)	57.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	24.50 in
Dimensions - (Shipping Unit Height)	57.50 in
Dimensions - (Shipping Unit Width)	18.50 in
Distribution Shipping Volume - (Unit)	26061.875 in <sup>3</sup>
Shipping Volume - (Unit)	26061.875 in <sup>3</sup>
Truck Factor	0
Volume - (Case)	26061.875 in <sup>3</sup>
Volume - (Distribution Shipping Unit)	26061.875 in <sup>3</sup>
Weight - (Case)	127.000 lb
Weight - (Distribution Shipping Unit)	127 lb
Weight - (Shipping Unit)	127.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Air Handler
Release Status	Active