

CAPFA2418C6

Generated from workbook row data

| Attribute | Value |
|---|---|
| Brand | Corporate |
| ProductCategory | Unitary |
| ProductClassPIM | Coil |
| System Family | Unitary Split System |
| Function Category | Cooling Only |
| Product Type | Equipment |
| Unit Type | Indoor |
| Market Type | Residential-Single Family |
| Product Family | CAPFA_410 |
| Series Name | CAPFA AlumaFin7™ |
| Short Description | CAPFA AlumaFin7™ Evaporator Coil, Upflow/Downflow, 2.0 Ton, R-410A |
| Family Description | CAPFA AlumaFin7™ Evaporator Coil |
| Product Benefits | <p>All-aluminum metallurgy provides superior corrosion resistance</p> <p>Compatible with R-410A refrigerant</p> <p>Multi-louvered aluminum fin design helps support efficient heat transfer</p> <p>Hydrophilic fins provide superior condensate management</p> <p>7mm sized grooved aluminum tubing for enhanced turbulence of refrigerant</p> <p>Vertical-flow design allows for upflow and downflow installation</p> <p>DecaBDE-free thermoplastic drain pan with secondary drain connections</p> <p>Coil rails to help ease of installation or removal of coils from cabinet</p> <p>Galvanized steel texture and parts used to help reduce corrosion on steel components</p> |
| Product Features - (Standard) | <p>Compact and lightweight all-aluminum evaporator coil with AlumaFin7™ technology</p> <p>Optimized for use with R-410A refrigerant</p> <p>Check flowrator for cooling applications</p> <p>Rust resistant, thermoplastic drain pans featuring a low water-retention design</p> <p>Foil-faced insulation covers the internal casing to reduce cabinet condensation</p> <p>Single-piece access panel with tight seal helps to keep conditioned air from escaping</p> <p>Seal tight customized suction and liquid grommets for easy installation and removal</p> <p>21" depth for easier attic access</p> <p>Vertical application</p> <p>Galvanized, leather grain-embossed finish</p> <p>AHRI certified</p> <p>ETL listed</p> |
| Installation Type | Ducted |
| Communication Feature | No |
| Export Control Classification Number - (ECCN) | EAR99 |
| Min Advertised Price | 466 \$ |
| Universal Product Code (UPC) | 663051629080 |

| Attribute | Value |
|-------------------------------------|---|
| Item Stocking Unit of Measure (UOM) | EA |
| Pallet Qty | 12 |
| Country of Origin | USA |
| US HTS Code | 8415.90.8020 |
| Canadian HTS Code | 8415.90.90.00 |
| Long Description | CAPFA AlumaFin7™ Cased Aluminum Evaporator Coil, Upflow/Downflow, 1.5<multisep/>2.0 Ton, 21 in Cabinet with Orifice Expansion, R-410A |
| ProductDescriptionPIM | 2.0t cased e coil flrt 18" |
| CoolingCapacityNominal | 24000 Btu/H |
| Producer | Yes |
| ProductIDBarcode | CAPFA2418C6 |
| ANSI | Yes |
| CabinetFinish | Painted |
| CasedvsUncased | Cased |
| DimensionsUnitDepth | 21 in |
| DimensionsUnitHeight | 18 in |
| DimensionsUnitWidth | 21 in |
| ETLListed | Yes |
| EvapCoilRows | 3 |
| EvapFinDensityFinsPerInch | 17 |
| ExpansionDevice | Orifice |
| IndoorOrificeSize | 0.051 in |
| PlenumOpeningWidth | 20 in |
| WeightUnit | 38 lb |
| Tonnage | 2 |
| TonnageRange | 1.5;2.0 |
| CondensateDrainOutlet | 3/4 in |
| PipeSizeGas | 3/4 in |
| PipeSizeLiquid | 3/8 in |
| RefrigerantType | R-410A |
| Proposition 65 Label | Yes |
| Carton Type | CTN |

| Attribute | Value |
|---|-----------------------------|
| Case Qty | 1 |
| Dimensions - (Case Depth) | 26.25 in |
| Dimensions - (Case Height) | 20.75 in |
| Dimensions - (Case Width) | 23.50 in |
| Dimensions - (Distribution Unit Depth) | 26.25 in |
| Dimensions - (Distribution Unit Height) | 20.75 in |
| Dimensions - (Distribution Unit Width) | 23.5 in |
| Dimensions - (Pallet Depth) | 54.00 in |
| Dimensions - (Pallet Height) | 66.75 in |
| Dimensions - (Pallet Width) | 50.00 in |
| Dimensions - (Shipping Unit Depth) | 26.25 in |
| Dimensions - (Shipping Unit Height) | 20.75 in |
| Dimensions - (Shipping Unit Width) | 23.50 in |
| Distribution Shipping Volume - (Unit) | 12800.15625 in ³ |
| Shipping Volume - (Unit) | 12800.156 in ³ |
| Truck Factor | 0 |
| Volume - (Case) | 12800.156 in ³ |
| Volume - (Distribution Shipping Unit) | 12800.15625 in ³ |
| Weight - (Case) | 43.000 lb |
| Weight - (Distribution Shipping Unit) | 43 lb |
| Weight - (Shipping Unit) | 43.000 lb |
| Registered Parts Warranty - Commercial | ALL PARTS - 5 YEARS PARTS |
| Registered Parts Warranty - Multi-Family | ALL PARTS - 10 YEARS PARTS |
| Registered Parts Warranty - Residential | ALL PARTS - 10 YEARS PARTS |
| Registered Unit Replacement Warranty - Multi-Family | 10 YEARS UNIT REPLACEMENT |
| Registered Unit Replacement Warranty - Commercial | 5 YEARS UNIT REPLACEMENT |
| Registered Unit Replacement Warranty - Residential | 10 YEARS UNIT REPLACEMENT |
| Standard Parts Warranty - Commercial | ALL PARTS - 5 YEARS PARTS |

| Attribute | Value |
|---|---|
| Standard Parts Warranty - Multi-Family | ALL PARTS - 5 YEARS PARTS |
| Standard Parts Warranty - Residential | ALL PARTS - 5 YEARS PARTS |
| Standard Unit Replacement Warranty - Commercial | 5 YEARS UNIT REPLACEMENT |
| Standard Unit Replacement Warranty - Multi-Family | 5 YEARS UNIT REPLACEMENT |
| Standard Unit Replacement Warranty- Residential | 5 YEARS UNIT REPLACEMENT |
| Ecomm Path Display | Equipment/Residential Split System/Coil |
| Release Status | Obsolete |