

CAPFA3022D3

Generated from workbook row data

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Coil
System Family	Unitary Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	CAPFA_32
Series Name	CAPFA AlumaFin7™
Short Description	CAPFA AlumaFin7™ Evaporator Coil, Upflow/Downflow, Ton, R-32
Family Description	CAPFA AlumaFin7™ Evaporator Coil
Product Features - (Standard)	All-Aluminum evaporator coil Optimized for use with R-32 refrigerant including circuits and manifolds R-32 sensor designed for the life span of the coil Factory-installed optimized metering device (piston) Standardized copper suction tube stub length 21" depth for easier attic access Single front access panel Foil-faced insulation covers the internal casing to reduce cabinet condensation Vertical application Galvanized, leather grain-embossed finish Rust resistant, thermoplastic drain pans featuring a low water-retention design DecaBDE-free thermoplastic drain pan with secondary drain connections Drain pan rails designed to remove and reposition coils with ease without compromising structural integrity UV-resistant drain pan AHRI certified ETL listed
Installation Type	Ducted
Communication Feature	No
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051696266
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	12
Country of Origin	USA

Attribute	Value
US HTS Code	8415.90.8020
Canadian HTS Code	8415.90.90.00
Long Description	CAPFA AlumaFin7™ Cased Aluminum Evaporator Coil, Upflow/Downflow, 2.5 Ton, 22 in Cabinet with Flowrator Expansion, R-32
ProductDescriptionPIM	2.5T Cased Upflow/Downflow R-32 Coil
Producer	No
ProductIDBarcode	CAPFA3022D3
PowerFrequency	60 Hz
PowerPhase	1 Ph
CabinetFinish	Painted
CasedvsUncased	Cased
DimensionsUnitDepth	24.5 in
DimensionsUnitHeight	21 in
DimensionsUnitWidth	22 in
EvapCoilRows	3
EvapFinDensityFinsPerInch	17
ExpansionDevice	Flowrator
TonnageRange	2.5
CondensateDrainOutlet	3/4 in
PipeSizeGas	3/4 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	27.00 in
Dimensions - (Case Height)	25.00 in
Dimensions - (Case Width)	26.00 in
Dimensions - (Distribution Unit Depth)	27 in
Dimensions - (Distribution Unit Height)	25 in
Dimensions - (Distribution Unit Width)	26 in
Dimensions - (Pallet Depth)	55.00 in

Attribute	Value
Dimensions - (Pallet Height)	78.00 in
Dimensions - (Pallet Width)	53.00 in
Dimensions - (Shipping Unit Depth)	27.00 in
Dimensions - (Shipping Unit Height)	25.00 in
Dimensions - (Shipping Unit Width)	26.00 in
Distribution Shipping Volume - (Unit)	17550 in ³
Shipping Volume - (Unit)	17550.000 in ³
Truck Factor	0
Volume - (Case)	17550.000 in ³
Volume - (Distribution Shipping Unit)	17550 in ³
Weight - (Case)	54.000 lb
Weight - (Distribution Shipping Unit)	54 lb
Weight - (Shipping Unit)	54.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Registered Unit Replacement Warranty - Multi-Family	10 YEARS UNIT REPLACEMENT
Registered Unit Replacement Warranty - Commercial	5 YEARS UNIT REPLACEMENT
Registered Unit Replacement Warranty - Residential	10 YEARS UNIT REPLACEMENT
Ecomm Path Display	Equipment/Residential Split System/Coil
Release Status	Active