

# CAPTA6034C3

Generated from workbook row data

Attribute	Value
Brand	Corporate
ProductCategory	Unitary
ProductClassPIM	Coil
System Family	Unitary Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	CAPTA_3
Series Name	CAPTA AlumaFin7™
Short Description	CAPTA AlumaFin7™ Evaporator Coil, Upflow/Downflow, Ton, R-32
Family Description	CAPTA AlumaFin7™ Evaporator Coil
Product Features - (Standard)	<p>All-Aluminum evaporator coil            Optimized for use with R-32 refrigerant including circuits and manifolds            R-32 sensor designed for the life span of the coil            Factory-installed thermal expansion valves for cooling and heat pump applications            Standardized copper suction tube stub length            Check flowrator for cooling and heat pump applications            Vertical application            21" depth for easier attic access            Single front access panel            Foil-faced insulation covers the internal casing to reduce cabinet condensation            Galvanized, leather grain-embossed finish            Rust resistant, thermoplastic drain pan featuring a low water-retention design            DecaBDE-free thermoplastic drain pan with secondary drain connections            Drain pan rails designed to remove and reposition coils with ease without compromising structural integrity            UV-resistant drain pan            AHRI certified            ETL Listed</p>
Installation Type	Ducted
Communication Feature	No
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051848290
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	8
Country of Origin	USA

Attribute	Value
Long Description	CAPTA AlumaFin7™ Cased Evaporator Coil, Upflow/Downflow, 5 Ton, 21 in Cabinet with TXV Expansion, R-32
ProductDescriptionPIM	5T Cased Upflow/Downflow R-32 Coil with TXV
ENERGYSTARCertified	No
Producer	No
ProductIDBarcode	CAPTA6034C3
CasedvsUncased	Cased
DimensionsUnitDepth	21 in
DimensionsUnitHeight	34 in
DimensionsUnitWidth	21 in
ExpansionDevice	TXV
IndoorOrificeSize	N/A in
WeightUnit	77 lb
TonnageRange	5
CondensateDrainOutlet	3/4 in
PipeSizeGas	7/8 in
PipeSizeLiquid	3/8 in
RefrigerantType	R-32
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	26.00 in
Dimensions - (Case Height)	36.00 in
Dimensions - (Case Width)	23.50 in
Dimensions - (Pallet Depth)	54.00 in
Dimensions - (Pallet Height)	78.00 in
Dimensions - (Pallet Width)	50.00 in
Dimensions - (Shipping Unit Depth)	26.00 in
Dimensions - (Shipping Unit Height)	36.00 in
Dimensions - (Shipping Unit Width)	23.50 in
Shipping Volume - (Unit)	21996.000 in <sup>3</sup>
Truck Factor	0

Attribute	Value
Volume - (Case)	21996.000 in <sup>3</sup>
Weight - (Case)	75.000 lb
Weight - (Shipping Unit)	75.000 lb
Ecomm Path Display	Equipment/Residential Split System/Coil