

# GC9S800804BN

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Gas Furnace
System Family	Unitary Split System
Function Category	Heating Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	GC9S80
Short Description	Goodman 80% AFUE Gas Furnace Multi-Speed, Single Stage
Model Efficiency	0.8
Family Description	Single-Stage Multi-Speed ECM Gas Furnace 80% AFUE
Product Benefits	Higher reliability and quality Durable and long igniter life Provisions for electronic air cleaner and humidifier Energy Efficient and quiet circulation Self-diagnostic control board with constant memory Simple installation and setup Quiet and simple operation
Product Features - (Standard)	Heavy-duty stainless-steel tubular heat exchanger "Silicon Nitride igniter" Color-coded low-voltage terminals Multi-speed ECM blower motor with continuous fan speed Fault code LED Output Single-Stage gas Valve Single-speed inducer draft blower
Installation Type	Ducted
Export Control Classification Number - (ECCN)	EAR99
Min Advertised Price	1138 \$
Universal Product Code (UPC)	663051627611
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	USA
US HTS Code	7322.90.0015
Canadian HTS Code	7322.90.10.21

Attribute	Value
Long Description	Goodman 80% AFUE Gas Furnace Multi-Speed, Single Stage, Downflow/Horizontal, 80,000 BTUH/H, Non-NOx
ProductDescriptionPIM	fer uf furnace
AFUE	0.8
CoolingCapacityNominal	48000 Btu/H
InstallationConfiguration	Downflow/Horizontal
Producer	Yes
ProductIDBarcode	GC9S800804BN
TemperatureRiseRangeHigh	35-65 °F
MaxOvercurrentProtection	15 A
MinCircuitAmps	12.45 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
AirFlowRateHighHeating	1238 ft <sup>3</sup> /min
DimensionsBlowerDiameter	10 in
DimensionsBlowerWidth	8 in
DimensionsUnitDepth	28 in
DimensionsUnitHeight	33-3/8 in
DimensionsUnitWidth	17-1/2 in
HeatExchangerType	Air Cooled
MotorSpeedType	Multi-Speed
NOxBurnerType	Non-NOx
WeightUnit	107 lb
BlowerMotorHorsePower	3/4 metric hp
HighFireInputCapacity	80000 Btu
HighFireOutputCapacity	64000
Tonnage	4
GasValveType	Single Stage
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1

Attribute	Value
Dimensions - (Case Depth)	30.00 in
Dimensions - (Case Height)	35.50 in
Dimensions - (Case Width)	18.50 in
Dimensions - (Distribution Unit Depth)	30 in
Dimensions - (Distribution Unit Height)	35.5 in
Dimensions - (Distribution Unit Width)	18.5 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	35.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	30.00 in
Dimensions - (Shipping Unit Height)	35.50 in
Dimensions - (Shipping Unit Width)	18.50 in
Distribution Shipping Volume - (Unit)	19702.5 in <sup>3</sup>
Shipping Volume - (Unit)	19702.500 in <sup>3</sup>
Truck Factor	0
Volume - (Case)	19702.500 in <sup>3</sup>
Volume - (Distribution Shipping Unit)	19702.5 in <sup>3</sup>
Weight - (Case)	108.000 lb
Weight - (Distribution Shipping Unit)	108 lb
Weight - (Shipping Unit)	108.000 lb
Registered Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS
Standard Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS

Attribute	Value
Ecomm Path Display	Equipment/Residential Split System/Gas Furnace
Release Status	Active