

# GLXS4BA4210

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Split Air Conditioner
System Family	Unitary Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	GLXS4B
Series Name	GLXS4B
Short Description	Goodman Split Air Conditioner 14.3 SEER2, Single Stage
Model Efficiency	14.3 SEER2
Family Description	Energy-Efficient Classic R-32 Split System Air Conditioner, 14.3 SEER2, 1½ To 5 Tons
Product Features - (Standard)	Energy-Efficient Compressor Fully charged for 15' of tubing length Copper tube/ enhanced aluminum fin coil-5mm diameter Factory-installed filter drier Sweat connection service valves with easy access to gauge ports Enclosed contactor with lug connection High-pressure switch Capacitors with extended life AHRI Certified ETL Listed
Cabinet Features	Removable grille-style top design compliant with UL 60335-2-40 Venturi for increased velocity of airflow Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval Wire fan discharge grille Steel louver coil guard Top and side maintenance access Single-panel access to controls with space provided for field-installed accessories When properly anchored, meets the 2023 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)
Communication Feature	No
Communication Feature Type	Non-Communicating
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051691667

Attribute	Value
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8085
Canadian HTS Code	8415.90.90.00
Long Description	Goodman Split Air Conditioner 14.3 SEER2, Single Stage, 3.5 Ton, Non-Communicating
ProductDescriptionPIM	14.3 SEER2 R-32 AC, 3.5T
CoolingCapacityNominal	42000 Btu/H
EER2HSVTC	11.7
EERHSVTC	11.7
ENERGYSTARCertified	No
SEER2HSVTC	14.3
InstallationConfiguration	Top Discharge
Producer	Yes
ProductIDBarcode	GLXS4BA4210
CoolingOperationRangeStdMax	125 °F
CoolingOperationRangeStdMin	55 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
MaxOvercurrentProtection	30 A
MinCircuitAmps	18.95 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208/240 V
RatedLoadAmps	14.4 A
CompressorStages	Single Stage
CompressorType	Scroll
DimensionsUnitDepth	35.5 in
DimensionsUnitHeight	35.75 in
DimensionsUnitWidth	35-1/2 in
MotorSpeedType	Single Speed

Attribute	Value
SoundPressureHighCooling	72 dBA
WeightUnit	72 lb
CoolingCapacityRated	40000 Btu/H
Tonnage	3.5
AdditionalRefrigerantCharge	0.64 lb
FactoryStdRefrigerantCharge	82.6 oz
MaxPipeLengthTotal	200 ft
MaxPipeLengthVertical	79 ft
PipeSizeGas	1-1/8 in
PipeSizeLiquid	3/8 in
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-32
ValveSizeLiquidOD	3/8 in
ValveSizeSuctionOD	7/8 in
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	38.50 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	38.5 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	38.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	38.50 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	52706.5 in <sup>3</sup>
Shipping Volume - (Unit)	52706.500 in <sup>3</sup>
Truck Factor	0

Attribute	Value
Volume - (Case)	52706.500 in <sup>3</sup>
Volume - (Distribution Shipping Unit)	52706.5 in <sup>3</sup>
Weight - (Case)	247.000 lb
Weight - (Distribution Shipping Unit)	247 lb
Weight - (Shipping Unit)	247.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Split Air Conditioner
Release Status	Active