

GLXS5BA4210

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Split Air Conditioner
System Family	Unitary Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	GLXS5
Series Name	GLXS5B
Short Description	Goodman Split Air Conditioner 15.2 SEER2, Single Stage
Model Efficiency	15.2 SEER2
Product Features - (Standard)	High-efficiency scroll compressor Factory-installed filter drier Fully charged for 15' of tubing length Copper tube/enhanced aluminum fin coil -5mm diameter on 1.5-3.0T Service valves with sweat connections and easy-to-access gauge ports Enclosed contactor with lug connection Ground lug connection High-pressure switch AHRI Certified ETL Listed
Cabinet Features	Removable grille-style top design compliant with UL 60335-2-40 Heavy-gauge galvanized-steel cabinet Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval Steel louver coil guard Single-panel access to controls with space provided for field-installed accessories When properly anchored, meets the 2023 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)
Communication Feature	No
Communication Feature Type	Non-Communicating
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051735507
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1

Attribute	Value
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
Long Description	Goodman Split Air Conditioner 15.2 SEER2, Single Stage, 3.5 Ton, Non-Communicating
ProductDescriptionPIM	15.2 SEER2 R-32 AC, 3.5 Ton
InstallationConfiguration	Top Discharge
Producer	Yes
ProductIDBarcode	GLXS5BA4210
CoolingOperationRangeStdMax	115 °F
CoolingOperationRangeStdMin	55 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	72 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
CompressorRLA	14.4 A
MaxOvercurrentProtection	30 A
MinCircuitAmps	19.3 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208/230 V
CompressorStages	Single Stage
CompressorType	Scroll
DimensionsUnitDepth	35.5 in
DimensionsUnitHeight	36.5 in
DimensionsUnitWidth	35-1/2 in
MotorSpeedType	Single Speed
SoundPressureHighCooling	73.8 dBA
Tonnage	3.5
FactoryStdRefrigerantCharge	141 oz
MaxPipeLengthTotal	79 ft
MaxPipeLengthVertical	50 ft

Attribute	Value
PipeSizeGas	1-1/8 in
PipeSizeLiquid	3/8 in
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-32
ValveSizeLiquidOD	3/8 in
ValveSizeSuctionOD	7/8 in
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	38.50 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in
Dimensions - (Distribution Unit Height)	38.5 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	38.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	38.50 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	52706.5 in ³
Shipping Volume - (Unit)	52706.500 in ³
Truck Factor	0
Volume - (Case)	52706.500 in ³
Volume - (Distribution Shipping Unit)	52706.5 in ³
Weight - (Case)	274.000 lb
Weight - (Distribution Shipping Unit)	274 lb
Weight - (Shipping Unit)	274.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS

Attribute	Value
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Split Air Conditioner
Release Status	Active