

GM9S921205DN

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Gas Furnace
System Family	Unitary Split System
Function Category	Heating Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	GM9S92
Short Description	Goodman 92% AFUE Gas Furnace Multi Speed ECM, Single Stage
Model Efficiency	0.92
Family Description	Single-Stage Multi-Speed ECM Gas Furnace Up to 92% AFUE
Product Benefits	High reliability and quality Faster condensate water drainage and no unit water leakage Durable and long igniter life Provisions for electronic air cleaner and humidifier Energy Efficient and quiet circulation Lower NOx emission Self-diagnostic control board with constant memory Simple installation and setup Quiet and simple operation
Product Features - (Standard)	Heavy-duty aluminized-steel tubular heat exchanger Stainless-steel sloped secondary heat exchanger "Silicon Nitride igniter" Color-coded low-voltage terminals Multi-speed ECM blower motor with continuous fan speed All models comply with California 40 ng/J Fault code LED Output Single-Stage gas Valve Single-speed inducer draft blower
Installation Type	Ducted
Export Control Classification Number - (ECCN)	EAR99
Min Advertised Price	1869 \$
Universal Product Code (UPC)	663051628519
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4

Attribute	Value
Country of Origin	USA
US HTS Code	7322.90.0015
Canadian HTS Code	7322.90.10.21
Long Description	Goodman 92% AFUE Gas Furnace Multi Speed ECM, Single Stage, Upflow/Horizontal, 120,000 BTUH/H, Low NOx
ProductDescriptionPIM	fer uf furnace
AFUE	0.92
CoolingCapacityNominal	60000 Btu/H
InstallationConfiguration	Upflow/Horizontal
Producer	Yes
ProductIDBarcode	GM9S921205DN
TemperatureRiseRangeHigh	35-65 °F
MaxOvercurrentProtection	25 A
MinCircuitAmps	16.7 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
DimensionsBlowerDiameter	11 in
DimensionsBlowerWidth	11 in
DimensionsUnitDepth	28 in
DimensionsUnitHeight	33-3/8 in
DimensionsUnitWidth	24-1/2 in
HeatExchangerType	Air Cooled
MotorSpeedType	Multi Speed ECM
NOxBurnerType	Low NOx
WeightUnit	154 lb
BlowerMotorHorsePower	1 metric hp
HighFireInputCapacity	120000 Btu
HighFireOutputCapacity	110520
GasValveType	Single Stage
Proposition 65 Label	Yes
Carton Type	CTN

Attribute	Value
Case Qty	1
Dimensions - (Case Depth)	30.00 in
Dimensions - (Case Height)	38.50 in
Dimensions - (Case Width)	25.50 in
Dimensions - (Distribution Unit Depth)	30 in
Dimensions - (Distribution Unit Height)	38.5 in
Dimensions - (Distribution Unit Width)	25.5 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	38.50 in
Dimensions - (Pallet Width)	51.00 in
Dimensions - (Shipping Unit Depth)	30.00 in
Dimensions - (Shipping Unit Height)	38.50 in
Dimensions - (Shipping Unit Width)	25.50 in
Distribution Shipping Volume - (Unit)	29452.5 in ³
Shipping Volume - (Unit)	29452.500 in ³
Truck Factor	0
Volume - (Case)	29452.500 in ³
Volume - (Distribution Shipping Unit)	29452.5 in ³
Weight - (Case)	150.000 lb
Weight - (Distribution Shipping Unit)	150 lb
Weight - (Shipping Unit)	150.000 lb
Registered Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	HEAT EXCHANGER - 79 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS ALL PARTS - 10 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS
Standard Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS

Attribute	Value
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Gas Furnace
Release Status	Active