

GMVC800804CN

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Gas Furnace
System Family	Unitary Split System
Function Category	Heating Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	GMVC80
Series Name	GMVC80
Short Description	Goodman 80% AFUE Gas Furnace Variable Speed, Two Stage
Model Efficiency	0.8
Family Description	ComfortBridge™-Compatible Two-Stage, Variable-Speed ECM Gas Furnace 80% AFUE
Product Benefits	<ol style="list-style-type: none"> 1. High reliability and quality 2. Airflow system gently ramps up or down according to heating or cooling demand and provides better comfort 3. Capable of using non communicating single-stage thermostats 4. Durable and long igniter life 5. Quiet and Economical heating 6. Operates on single-stage thermostats
Product Features - (Standard)	<ol style="list-style-type: none"> 1. Heavy-duty aluminized-steel tubular heat exchanger 2. Efficient and quiet variable-speed Blower 3. ComfortBridge™ Communicating System compatible 4. Commissioning and diagnostics via on board Bluetooth with the CoolCloud™ phone and tablet application 5. Silicon Nitride igniter 6. Two-Stage gas valve
Cabinet Features	<ol style="list-style-type: none"> 1. Multi-position installation: upflow, horizontal left or right 2. Convenient left or right connection for gas and electrical service 3. Cabinet air leakage (Qleak) less than or equal to 2% 4. Fully insulated heat exchanger and blower section 5. Bottom or side return air applications 6. Heavy-gage steel cabinet with durable finish
Installation Type	Ducted
Communication Feature	Yes
Communication Feature Type	ComfortBridge Technology compatible

Attribute	Value
Export Control Classification Number - (ECCN)	EAR99
FER Compliant	Yes
Min Advertised Price	1776 \$
Serialized Flag	Yes
Universal Product Code (UPC)	663051617759
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	USA
US HTS Code	7322.90.0015
Canadian HTS Code	7322.90.00.21
Long Description	Goodman 80% AFUE Gas Furnace Variable Speed, Two Stage, Upflow/Horizontal, 80,000 BTUH/H, Non-NOx
ProductDescriptionPIM	fer uf furnace
AFUE	0.8
AHRReferenceNumber	204633306
CoolingCapacityNominal	48000 Btu/H
ENERGYSTARCertified	No
InstallationConfiguration	Upflow/Horizontal
Producer	Yes
ProductIDBarcode	GMVC800804CN
TemperatureRiseRangeHigh	25-55 °F
TemperatureRiseRangeLow	25-55 °F
CurrentType	AC
MaxOvercurrentProtection	15 A
MinCircuitAmps	7.75 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
AirFlowRateHighHeating	1400 ft³/min
AirFlowRateLowHeating	980 ft³/min
ANSI	Yes
BlowerAvailableACTonnageHigh	4 Tonnage

Attribute	Value
BlowerAvailableACTonnageLow	3 Tonnage
BlowerMotorRPM	1200 r/min
DimensionsBlowerDiameter	11 in
DimensionsBlowerWidth	10 in
DimensionsUnitDepth	28 in
DimensionsUnitHeight	33.3 in
DimensionsUnitWidth	21 in
ETLListed	Yes
ExternalStaticPressureRated	0.5
FilterQuantity	1
FilterSizeMin	16x25
HeatExchangerType	Gas
MinimumClearancestoCombustibleMaterials	1 ft
MotorSpeedType	Variable Speed
NOxBurnerType	Non-NOx
NumberOfBurners	4
WeightUnit	118 lb
BlowerMotorHorsePower	1/2 metric hp
HighFireInputCapacity	80000 Btu
HighFireOutputCapacity	64000
LowFireInputCapacity	56000
LowFireOutputCapacity	44800
Tonnage	4
GasValveType	Two Stage
VentDiameter	4 in
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	30.00 in
Dimensions - (Case Height)	35.50 in
Dimensions - (Case Width)	22.00 in

Attribute	Value
Dimensions - (Distribution Unit Depth)	28 in
Dimensions - (Distribution Unit Height)	33.5 in
Dimensions - (Distribution Unit Width)	21 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	35.50 in
Dimensions - (Pallet Width)	44.00 in
Dimensions - (Shipping Unit Depth)	30.00 in
Dimensions - (Shipping Unit Height)	35.50 in
Dimensions - (Shipping Unit Width)	22.00 in
Distribution Shipping Volume - (Unit)	19698 in ³
Shipping Volume - (Unit)	23430.000 in ³
Truck Factor	0
Volume - (Case)	23430.000 in ³
Volume - (Distribution Shipping Unit)	19698 in ³
Weight - (Case)	115.000 lb
Weight - (Distribution Shipping Unit)	118 lb
Weight - (Shipping Unit)	115.000 lb
Registered Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	HEAT EXCHANGER - 79 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS ALL PARTS - 10 YEARS PARTS
Registered Unit Replacement Warranty - Residential	HEAT EXCHANGER - 10 YEARS UNIT REPLACEMENT HEAT EXCHANGER - 10 YEARS UNIT REPLACEMENT HEAT EXCHANGER - 10 YEARS UNIT REPLACEMENT
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Standard Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Gas Furnace

Attribute	Value
Release Status	Active