

GR9S920803BN

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Gas Furnace
System Family	Unitary Split System
Function Category	Heating Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	GR9S92
Short Description	Goodman 92% AFUE Gas Furnace Multi-Speed, Single Stage
Model Efficiency	0.92
Family Description	Single-Stage Multi-Speed ECM Gas Furnace Up to 92% AFUE
Product Benefits	High reliabilitynd quality Faster condensate water drainagend no unit water leakage Durablend long igniter life Provisions for electronicir cleanernd humidifier Energy Efficientnd quiet circulation Lower NOx emission Self-diagnostic control board with constant memory Simple installationnd setup Quietnd simple operation
Product Features - (Standard)	Heavy-duty luminized-steel tubular heat exchanger Stainless-steel sloped secondary heat exchanger "Silicon Nitride igniter" Color-coded low-voltage terminals Multi-speed ECM blower motor with continuous fan speed All models comply with California 40 ng/J Fault code LED Output Single-Stage gas Valve Single-speed inducer draft blower
Installation Type	Ducted
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051686168
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Country of Origin	USA

Attribute	Value
US HTS Code	7322.90.0015
Canadian HTS Code	7322.90.10.21
Long Description	Goodman 92% AFUE Gas Furnace Multi-Speed, Single Stage, Upflow/Horizontal, 80,000 BTUH/H, Non-NOx
ProductDescriptionPIM	fer uf furnace
AFUE	0.92
CoolingCapacityNominal	36000 Btu/H
InstallationConfiguration	Upflow/Horizontal
Producer	Yes
ProductIDBarcode	GR9S920803BN
TemperatureRiseRangeHigh	35-65 °F
MaxOvercurrentProtection	15 A
MinCircuitAmps	9.8 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
AirFlowRateHighHeating	1373.35 ft ³ /min
DimensionsBlowerDiameter	10 in
DimensionsBlowerWidth	8 in
DimensionsUnitDepth	28-7/8 in
DimensionsUnitHeight	34-1/2 in
DimensionsUnitWidth	17-1/2 in
HeatExchangerType	Gas
MotorSpeedType	Multi-Speed
NOxBurnerType	Non-NOx
WeightUnit	117 lb
BlowerMotorHorsePower	0.5 metric hp
HighFireInputCapacity	80000 Btu
HighFireOutputCapacity	73680
Tonnage	3
GasValveType	Single Stage
Proposition 65 Label	Yes

Attribute	Value
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	30.00 in
Dimensions - (Case Height)	38.50 in
Dimensions - (Case Width)	18.50 in
Dimensions - (Distribution Unit Depth)	30 in
Dimensions - (Distribution Unit Height)	38.5 in
Dimensions - (Distribution Unit Width)	18.5 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	38.50 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	30.00 in
Dimensions - (Shipping Unit Height)	38.50 in
Dimensions - (Shipping Unit Width)	18.50 in
Distribution Shipping Volume - (Unit)	21367.5 in ³
Shipping Volume - (Unit)	21367.500 in ³
Truck Factor	0
Volume - (Case)	21367.500 in ³
Volume - (Distribution Shipping Unit)	21367.5 in ³
Weight - (Case)	118.500 lb
Weight - (Distribution Shipping Unit)	118.5 lb
Weight - (Shipping Unit)	118.500 lb
Registered Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS
Standard Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS

Attribute	Value
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Gas Furnace
Release Status	Active