

GR9S920805CN

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Gas Furnace
System Family	Unitary Split System
Function Category	Heating Only
Product Type	Equipment
Unit Type	Indoor
Market Type	Residential-Single Family
Product Family	GR9S92
Short Description	Goodman 92% AFUE Gas Furnace Multi-Speed, Single Stage
Model Efficiency	0.92
Family Description	Single-Stage Multi-Speed ECM Gas Furnace Up to 92% AFUE
Product Benefits	<p>High reliability and quality</p> <p>Faster condensate water drainage and no unit water leakage</p> <p>Durable long igniter life</p> <p>Provisions for electronic cleaner and humidifier</p> <p>Energy Efficient and quiet circulation</p> <p>Lower NOx emission</p> <p>Self-diagnostic control board with constant memory</p> <p>Simple installation and setup</p> <p>Quiet and simple operation</p>
Product Features - (Standard)	<p>Heavy-duty luminized-steel tubular heat exchanger</p> <p>Stainless-steel sloped secondary heat exchanger</p> <p>"Silicon Nitride igniter"</p> <p>Color-coded low-voltage terminals</p> <p>Multi-speed ECM blower motor with continuous fan speed</p> <p>All models comply with California 40 ng/J</p> <p>Fault code LED Output</p> <p>Single-Stage gas Valve</p> <p>Single-speed inducer draft blower</p>
Installation Type	Ducted
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051686182
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	4
Long Description	Goodman 92% AFUE Gas Furnace Multi-Speed, Single Stage, Upflow/Horizontal, 80,000 BTUH/H, Non-NOx

Attribute	Value
ProductDescriptionPIM	fer uf furnace
AFUE	0.92
CoolingCapacityNominal	60000 Btu/H
InstallationConfiguration	Upflow/Horizontal
Producer	No
ProductIDBarcode	GR9S920805CN
TemperatureRiseRangeHigh	25-55 °F
MaxOvercurrentProtection	25 A
MinCircuitAmps	16.4 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	115 V
AirFlowRateHighHeating	1823.15 ft ³ /min
DimensionsBlowerDiameter	11 in
DimensionsBlowerWidth	10 in
DimensionsUnitDepth	28-7/8 in
DimensionsUnitHeight	34-1/2 in
DimensionsUnitWidth	21 in
HeatExchangerType	Gas
MotorSpeedType	Multi-Speed
NOxBurnerType	Non-NOx
WeightUnit	140 lb
BlowerMotorHorsePower	1 metric hp
HighFireInputCapacity	80000 Btu
HighFireOutputCapacity	73680
Tonnage	5
GasValveType	Single Stage
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	30.00 in
Dimensions - (Case Height)	38.50 in

Attribute	Value
Dimensions - (Case Width)	22.00 in
Dimensions - (Distribution Unit Depth)	30 in
Dimensions - (Distribution Unit Height)	38.5 in
Dimensions - (Distribution Unit Width)	22 in
Dimensions - (Pallet Depth)	60.00 in
Dimensions - (Pallet Height)	38.50 in
Dimensions - (Pallet Width)	44.00 in
Dimensions - (Shipping Unit Depth)	30.00 in
Dimensions - (Shipping Unit Height)	38.50 in
Dimensions - (Shipping Unit Width)	22.00 in
Distribution Shipping Volume - (Unit)	25410 in ³
Shipping Volume - (Unit)	25410.000 in ³
Truck Factor	0
Volume - (Case)	25410.000 in ³
Volume - (Distribution Shipping Unit)	25410 in ³
Weight - (Case)	132.000 lb
Weight - (Distribution Shipping Unit)	140.09 lb
Weight - (Shipping Unit)	132.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Registered Parts Warranty - Residential	HEAT EXCHANGER - 20 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 20 YEARS PARTS ALL PARTS - 10 YEARS PARTS HEAT EXCHANGER - 79 YEARS PARTS
Standard Parts Warranty - Commercial	HEAT EXCHANGER - 20 YEARS PARTS;ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS;HEAT EXCHANGER - 20 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Gas Furnace
Release Status	Active