

GSXH502410

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Split Air Conditioner
System Family	Unitary Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	GSXH5
Series Name	GSXH5
Short Description	Goodman Split Air Conditioner 15.2 SEER2, Single Stage
Model Efficiency	15.2 SEER2
Family Description	High-Efficiency Split System Air Conditioner, Up to 15.2 SEER2
Product Benefits	Meets the 2023 M1 Test Standards
Product Features - (Standard)	High-efficiency scroll compressor Copper tube/enhanced aluminum fin coil -5mm diameter on 1.5-3.0T Fully charged for 15' of tubing length Factory-installed filter drier Service valves with sweat connections and easy-to-access gauge ports Contactor with lug connection Ground lug connection AHRI Certified, ETL Listed
Cabinet Features	Removable grille-style top design compliant with UL 60335-2-40 Venturi for increased velocity of airflow Heavy-gauge galvanized-steel cabinet Attractive Architectural Gray powder-paint finish with 500-hour salt-spray approval Steel louver coil guard Rust-resistant coated screws Single-panel access to controls with space provided for field-installed accessories When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)
Installation Type	Ducted
Communication Feature	No
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051628939

Attribute	Value
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	2
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
Long Description	Goodman Split Air Conditioner 15.2 SEER2, Single Stage, 2 Ton,
ProductDescriptionPIM	15.2 SEER2 AC, 2.0T
InstallationConfiguration	Top Discharge
Producer	Yes
ProductIDBarcode	GSXH502410
CompressorLRA	59.5 A
CompressorRLA	11.5 A
MaxOvercurrentProtection	25 A
MaxVoltage	253 V
MinCircuitAmps	15.3 A
MinVoltage	197 V
OutdoorFLA	0.95 A
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208/230 V
CompressorStages	Single Stage
CompressorType	Scroll
EnergySource	Electric
ExpansionDevice	TXV
MotorSpeedType	Single Speed
CondenserFanHorsepower	1/6 metric hp
Tonnage	2
FactoryStdRefrigerantCharge	72 oz
RefrigerantType	R-410A
ValveConnectionType	Front-Seated
Proposition 65 Label	Yes
Carton Type	CTN

Attribute	Value
Case Qty	1
Dimensions - (Case Depth)	30.50 in
Dimensions - (Case Height)	34.50 in
Dimensions - (Case Width)	30.00 in
Dimensions - (Distribution Unit Depth)	35.5 in
Dimensions - (Distribution Unit Height)	35.75 in
Dimensions - (Distribution Unit Width)	35.5 in
Dimensions - (Pallet Depth)	30.50 in
Dimensions - (Pallet Height)	34.50 in
Dimensions - (Pallet Width)	60.00 in
Dimensions - (Shipping Unit Depth)	30.50 in
Dimensions - (Shipping Unit Height)	34.50 in
Dimensions - (Shipping Unit Width)	30.00 in
Distribution Shipping Volume - (Unit)	45053.93 in ³
Shipping Volume - (Unit)	31567.500 in ³
Truck Factor	0
Volume - (Case)	31567.500 in ³
Volume - (Distribution Shipping Unit)	45053.93 in ³
Weight - (Case)	159.000 lb
Weight - (Distribution Shipping Unit)	193 lb
Weight - (Shipping Unit)	159.000 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	ALL PARTS - 10 YEARS PARTS
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Split Air Conditioner
Release Status	Obsolete