

GSXV906010

Generated from workbook row data

Attribute	Value
Brand	Goodman
ProductCategory	Unitary
ProductClassPIM	Split Air Conditioner
System Family	Unitary Split System
Function Category	Cooling Only
Product Type	Equipment
Unit Type	Outdoor
Market Type	Residential-Single Family
Product Family	GSXV9
Series Name	GXSV9
Short Description	Goodman Split Air Conditioner 19.2 SEER2, Variable
Model Efficiency	19.2 SEER2
Family Description	High-Efficiency, Communicating, Variable-Speed, Inverter Driven Split System Air Conditioner, Up to 22.5 SEER2
Product Benefits	Meets the 2023 M1 Test Standards
Product Features - (Standard)	<p>Variable-speed swing and scroll compressors High-density compressor sound blanket Integrated communicating ComfortBridge™ Technology Variable-speed, quiet DC outdoor fan motor Control algorithmic logic In communicating mode, only two low-voltage wires to outdoor unit required Commissioning and diagnostics via indoor board Bluetooth with the CoolCloud™ phone and tablet application Diagnostic indicator lights, seven-segment LED display, and fault code storage Inside intelligence for diagnostics Field-selectable boost mode increases compressor speed during unusually high loads Field-installed bi-flow filter drier Coil and ambient temperature sensors Suction pressure transducer Sweat connection service valves with easy access to gauge ports AHRI Certified ETL Listed</p>
Cabinet Features	<p>Heavy-gauge galvanized-steel cabinet Removable grille-style top design compliant with UL 60335-2-40 Venturi for increased velocity of airflow Custom Nickel Gray powder-paint finish Wire fan discharge grille Steel louver coil guard Top and side maintenance access Single-panel access to controls with space provided for field-installed accessories When properly anchored, meets the 2020 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)</p>

Attribute	Value
Installation Type	Ducted
Communication Feature	Yes
Communication Feature Type	ComfortBridge Technology compatible
DOE Regional Compliance	All
Export Control Classification Number - (ECCN)	EAR99
Universal Product Code (UPC)	663051639775
Item Stocking Unit of Measure (UOM)	EA
Pallet Qty	1
Country of Origin	USA
US HTS Code	8415.90.8070
Canadian HTS Code	8415.90.90.00
Long Description	Goodman Split Air Conditioner 19.2 SEER2, Variable, 5 Ton, ComfortBridge Technology compatible
ProductDescriptionPIM	19.2 seer2 ac inverter, 5 ton
CoolingCapacityNominal	60000 Btu/H
EER2HSVTC	12.4
EERHSVTC	12.4
ENERGYSTARCertified	Yes
SEER2HSVTC	19
InstallationConfiguration	Top Discharge
Producer	Yes
ProductIDBarcode	GSXV906010
CoolingOperationRangeStdMax	125 °F
CoolingOperationRangeStdMin	0 °F
RatedCoolingConditionAmbientDB	95 °F
RatedCoolingConditionAmbientWB	75 °F
RatedCoolingConditionRoomDB	80 °F
RatedCoolingConditionRoomWB	67 °F
CompressorRLA	28.6 A
CurrentType	AC
MaxOvercurrentProtection	35 A
MaxVoltage	253 V

Attribute	Value
MinVoltage	197 V
PowerFrequency	60 Hz
PowerPhase	1 Ph
PowerVoltage	208/230 V
RatedLoadAmps	28.6 A
CompressorStages	Variable
CompressorType	Inverter
DimensionsUnitDepth	35.5 in
DimensionsUnitHeight	41.75 in
DimensionsUnitWidth	35-1/2 in
EnergySource	Electric
ExpansionDevice	TXV
MotorSpeedType	Multi-Speed
SoundPressureHighCooling	75 dBA
CoolingCapacityRated	52000 Btu/H
Tonnage	5
AdditionalRefrigerantCharge	0.6 lb
FactoryStdRefrigerantCharge	246 oz
MaxPipeLengthTotal	200 ft
MaxPipeLengthVertical	90 ft
PipeSizeLiquid	3/8 in
RefrigerantPreChargedLineLength	15 ft
RefrigerantType	R-410A
ValveSizeLiquidOD	3/8 in
ValveSizeSuctionOD	7/8 in
Proposition 65 Label	Yes
Carton Type	CTN
Case Qty	1
Dimensions - (Case Depth)	37.00 in
Dimensions - (Case Height)	44.00 in
Dimensions - (Case Width)	37.00 in
Dimensions - (Distribution Unit Depth)	37 in

Attribute	Value
Dimensions - (Distribution Unit Height)	44 in
Dimensions - (Distribution Unit Width)	37 in
Dimensions - (Pallet Depth)	37.00 in
Dimensions - (Pallet Height)	44.00 in
Dimensions - (Pallet Width)	37.00 in
Dimensions - (Shipping Unit Depth)	37.00 in
Dimensions - (Shipping Unit Height)	44.00 in
Dimensions - (Shipping Unit Width)	37.00 in
Distribution Shipping Volume - (Unit)	60236 in ³
Shipping Volume - (Unit)	60236.000 in ³
Truck Factor	0
Volume - (Case)	60236.000 in ³
Volume - (Distribution Shipping Unit)	60236 in ³
Weight - (Case)	330.090 lb
Weight - (Distribution Shipping Unit)	330.09 lb
Weight - (Shipping Unit)	330.090 lb
Registered Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Registered Parts Warranty - Multi-Family	ALL PARTS - 10 YEARS PARTS
Registered Parts Warranty - Residential	COMPRESSORS - 10 YEARS PARTS ALL PARTS - 10 YEARS PARTS ALL PARTS - 10 YEARS PARTS COMPRESSORS - 10 YEARS PARTS ALL PARTS - 10 YEARS PARTS COMPRESSORS - 10 YEARS PARTS
Registered Unit Replacement Warranty - Residential	COMPRESSORS - 10 YEARS UNIT REPLACEMENT COMPRESSORS - 10 YEARS UNIT REPLACEMENT COMPRESSORS - 10 YEARS UNIT REPLACEMENT
Standard Parts Warranty - Commercial	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Multi-Family	ALL PARTS - 5 YEARS PARTS
Standard Parts Warranty - Residential	ALL PARTS - 5 YEARS PARTS
Ecomm Path Display	Equipment/Residential Split System/Split Air Conditioner
Release Status	Obsolete