

N100

Source column: Item Number

Attribute	Value
Brand	Honeywell Home
Product Taxonomy Node	RMH Root.Controls.Thermostats
Pro Product Short Description	<p><p>The Honeywell Home FocusPRO® N100 is designed for pro ease-of-use and profitability. It reduces job complexities and time on-site while supporting recurring business thanks to its broad system compatibility, UWP® wall plate, large display and clear font, snap-on private label, and competitive price.</p></p> <p><p>Private Label Program for Contractors</p></p> <p><p>Customize product with your company contact info. The interchangeable, snap-on accent piece simplifies the private label process, so you can focus on supporting customers while improving retention and recurring business.</p></p>
Pro Product Detail Page Title	N100 FocusPro Non-Programmable Thermostat
Pro Product Breadcrumb Name	N100 FocusPro Non-Programmable Thermostat
Pro Product Web Overview	<p><p>The FocusPRO® N100 Non-Programmable Thermostat is designed for those who prefer manual control. It has an intuitive interface that makes it easy to navigate as well as a large display with clear font and an optional always-on backlight when hardwired.</p></p> <ul style="list-style-type: none"> Supports single-stage 1H/1C for TH1110U4000/U or up to 3H/2C heat pump and 2H/2C conventional for TH1320U4002/U or up to 2H/1C heat pump and 1H/1C conventional for TH1210U4001/U UWP® wall plate supports speedy installation and easy upgrade Private label with customized snap-on accent piece Large display with clear font Optional always-on backlight when hardwired Customizable display settings Intuitive interface for easy navigation Choose to receive filter reminders Heat low limit defaults to 40°F (4°C) but configurable to 32°F (0°C) for garage applications Dual fuel compatible* Wired outdoor sensor compatible* Fan lockout after cool call option 5-year warranty <p><p>*TH1320 and TH1210 models</p></p>
LOB	Comfort
Temperature Accuracy	1 °F 0.5 °C
Number of Batteries	2

Attribute	Value
Display Type	LCD Screen
Operating Relative Humidity (Max)	90% RH, non-condensing
Operating Relative Humidity (Min)	5% RH, non-condensing
Heat-Cool Changeover	Auto or Manual
Thermostat Type	Non programmable Digital
Works With Resideo App	No
Compatible Third Party App	No
SDS-Safety Data Sheet	No