

S9200

Source column: Item Number

| Attribute | Value |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Brand | Resideo |
| Product Taxonomy Node | RMH Root.Controls.Burner & Ignition Controls |
| Warranty | 1 Year |
| Pro Product Short Description | <p><p>Multiple Systems, One Control</p> <p>These integrated furnace controls offer compatibility and diagnostics for multiple systems, replacing a large number of furnace control models in single-stage warm air furnaces. The furnace control works with 120 VAC hot surface igniters and includes instructions and special wire harnesses for easy replacement.</p></p> |
| Pro Product Detail Page Title | S9200 Universal Hot Surface Ignition Integrated Furnace Control |
| Pro Product Breadcrumb Name | S9200 Universal Hot Surface Ignition Integrated Furnace Control |
| Pro Product Web Overview | <p><p>Our integrated furnace controls were designed to keep you on the job—not waiting for replacement parts—and moving forward by offering a board that works for nearly every system. The S9200 hot surface ignition integrated furnace control replaces over 195 existing furnace control models. With a 120 VAC hot surface igniter, this control board works in single-stage warm air furnaces. Includes easy-to-read instructions and special wire harnesses for a quick install.</p> Replaces over 195 existing furnace controls Controls circulating fan motor based on appliance requirements with a conventional low voltage thermostat Cross reference and wire harnesses included Main burner ignition using a 120V hot surface igniter Flame rectification circuit to monitor flame presence Monitoring of system pressure switch, high temperature limit, and rollout functions Appliance operation and safety requirements controlled via microprocessor LED system status, performance, and diagnostic indication Twinning capability </p> |
| LOB | RTS |
| Compatible With | 24Vac redundant, direct ignition gas control rated at 1.5A or less. Honeywell VR8205 recommended Resideo VR8205 recommended |
| Ignitor Electrical Rating | 5 A resistive @ 120VAC |
| Cool Fan Off Delay Timing | 0 or 60 seconds |
| Cool Fan On Delay Timing | 5 seconds |

| Attribute | Value |
|-----------------------------|-----------------------------|
| Heat Fan Off Delay Timing | 60, 90, 120, or 180 Seconds |
| Heat Fan On Delay Timing | 30 or 60 seconds |
| Ignition System Type | Hot Surface Ignition |
| Flame Failure Response Time | 2 Seconds max @ 1 μ A |
| Ignition Trial Time | 4, 6, or 8 seconds |
| Works With Resideo App | No |
| Compatible Third Party App | No |