

# VR4300

Source column: Item Number

Attribute	Value
Brand	Resideo
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Pro Product Short Description	Combination gas control for use in 120 Vac, gas-fired, standing pilot appliances with capacities from 30 to 300 cfh.
Pro Product Detail Page Title	VR4300 Combination Gas Control for use in gas-fired, standing pilot appliances
Pro Product Breadcrumb Name	VR4300 Combination Gas Control
Pro Product Web Overview	<p>&lt;p&gt;Combination gas control for use in 120 Vac, gas-fired, standing pilot appliances with capacities from 30 to 300 cfh. Control includes safety shutoff, manual valve, two automatic operators, pressure regulator and pilot adjustment. Compact size. Provides two automatic valves. Solenoid operated first automatic valve opens on thermostat call for heat, closes when call for heat ends. Diaphragm-operated second automatic valve opens under control of regulator; closes if gas or power supply is interrupted. Meets codes requiring dual safety shut-off. Natural to LP and LP to Natural conversion kits available for standard and slow opening gas valves. All adjustments, wiring connections and pilot outlet are accessible from top of control. Adjustable servo regulator effectively maintains almost constant gas output pressure under wide fluctuations in gas supply pressure. Compatible with ECO connector. LITE-RITE (OFF-PILOT-ON) lighting sequence.&lt;/p&gt;</p>
LOB	RTS
Compatible With	120 V AC, gas-fired, standing pilot appliances with capacities from 30 to 300 cfh
Works With Resideo App	No
Works With Resideo Applications	No
Compatible Third Party App	No
Pressure Rating	3.5 kPa 1/2 psi