

# VR8200

Source column: Item Number

Attribute	Value
Brand	Resideo
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Warranty	1 Year
Pro Product Short Description	<p>&lt;p&gt;&lt;strong&gt;Versatile Gas Valves&lt;/strong&gt;&lt;/p&gt; &lt;p&gt;These gas valves from Resideo are for use in 24 V AC, gas-fired, standing pilot appliances with capacities from 20 to 200 cfh.&lt;/p&gt;</p>
Pro Product Detail Page Title	VR8200 Gas Valves for Standing Pilot Appliances
Pro Product Breadcrumb Name	Gas Valves for Standing Pilot Appliances
Pro Product Web Overview	<p>&lt;p&gt;Combination gas control for use in 24 Vac gas-fired, standing pilot appliances with capacities from 30 to 300 cfh.&lt;/p&gt; &lt;ul&gt; &lt;li&gt;Control includes safety shutoff, manual valve, two automatic operators, pressure regulator and pilot adjustment.&lt;/li&gt; &lt;li&gt;Compact size.&lt;/li&gt; &lt;li&gt;Provides two automatic valves.&lt;/li&gt; &lt;li&gt;Solenoid operated first automatic valve opens on thermostat call for heat, closes when call for heat ends.&lt;/li&gt; &lt;li&gt;Diaphragm-operated second automatic valve opens under control of regulator; closes if gas or power supply is interrupted.&lt;/li&gt; &lt;li&gt;Meets codes requiring dual safety shut-off.&lt;/li&gt; &lt;li&gt;Natural to LP and LP to Natural conversion kits available for standard and slow opening gas valves.&lt;/li&gt; &lt;li&gt;All adjustments, wiring connections and pilot outlet are accessible from top of control.&lt;/li&gt; &lt;li&gt;Adjustable servo regulator effectively maintains almost constant gas output pressure under wide fluctuations in gas supply pressure.&lt;/li&gt; &lt;/ul&gt;</p>
LOB	RTS
Compatible With	24 V AC gas-fired, standing pilot appliances with capacities from 30 to 300 cfh
Works With Resideo App	No
Works With Resideo Applications	No
Compatible Third Party App	No
Pressure Rating	1/2 psi