

# VR8205

Source column: Item Number

Attribute	Value
Brand	Resideo
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Pro Product Short Description	Combination gas controls for use with hot surface/direct spark systems in 24 Vac, gas-fired appliances with capacities from 30 to 415 cfh.
Pro Product Detail Page Title	VR8205 Direct Ignition Combination Gas Controls
Pro Product Breadcrumb Name	VR8205 Direct Ignition Combination Gas Controls
Pro Product Web Overview	<p>&lt;p&gt;Combination gas controls for use with hot surface/direct spark systems in 24 Vac, gas-fired appliances with capacities from 30 to 415 cfh. Controls include manual valve, two automatic operators, and pressure regulator. Provide two automatic valves. Solenoid operated first automatic valve opens on thermostat call for heat; closes when call for heat ends. Diaphragm operated second automatic valve opens under control of the regulator; closes if gas or power supply is interrupted. Meet codes requiring dual safety shutoff. Natural to LP and LP to Natural conversion kits available for standard and slow opening gas valves. All adjustments, wiring connections and pilot outlet are accessible from top of control. ON-OFF lighting sequence.&lt;/p&gt;</p>
LOB	RTS
Compatible With	Hot surface/direct spark systems in 24 V AC, gas-fired appliances with capacities from 30 to 415 cfh
Works With Resideo App	No
Works With Resideo Applications	No
Compatible Third Party App	No