

VR8304

Source column: Item Number

Attribute	Value
Brand	Resideo
Product Taxonomy Node	RMH Root.Valves.Fuel Control Valves.Gas Valves
Warranty	1 Year
Pro Product Short Description	<p><p>Your Go-To Pilot Solution</p> <p>These Intermittent Pilot Combination Gas Controls from Resideo are specifically designed for gas-fired appliances with up to 415 ft3/hr capacity at 1 in. wc pressure drop (8.5 m3/hr at 0.25 kPa) on natural gas.</p></p>
Pro Product Detail Page Title	VR8304 Intermittent Pilot Combination Gas Controls
Pro Product Breadcrumb Name	VR8304 Intermittent Pilot Combination Gas Controls
Pro Product Web Overview	<p><p>Reliability You Can Count On</p> <p>These Intermittent Pilot Combination Gas Controls from Resideo have a 3/4 in inlet and 3/4 in. outlet for use in 24 V AC, gas-fired, intermittent pilot appliances with capacities from 30 to 415 cfh.</p> <p>There are two automatic valves: the solenoid-operated first automatic valve opens on thermostat call for heat, and closes when the call for heat ends. The diaphragm-operated second automatic valve opens under control of a regulator, and closes if the gas or power supply is interrupted.</p> <p>Features include:</p> Controls include safety shutoff, manual valve, two automatic operators, pressure regulator and pilot adjustment Compact size Two automatic valves Solenoid operated first automatic valve opens on thermostat call for heat; closes when call for heat ends Diaphragm-operated second automatic valve opens under control of regulator; closes if gas or power supply is interrupted Meet codes requiring dual safety shutoff Natural to LP and LP to natural conversion kits available for standard and slow opening gas valves All adjustments, wiring connections and pilot outlet are accessible from top of control Adjustable regulator effectively maintains almost constant gas output pressure under wide fluctuations in gas supply pressure Compatible with ECO connector ON-OFF lighting sequence </p>
LOB	RTS
Compatible With	24 V AC, gas-fired, standing pilot appliances with capacities from 30 to 415 cfh

Attribute	Value
Works With Resideo App	No
Works With Resideo Applications	No
Compatible Third Party App	No
Pressure Rating	1/2 psi 3.5 kPa